

72" Eight Blade Ceiling Fan

 Ceiling mounted • Damp location listed 

Description:

Enjoy spending a comfortable evening in your favorite large living area as you are kept cool by a beautiful and expansive Vast ceiling fan. A refreshing airflow cascades down from the fan's Black blades that are complemented by the handsome Black finish. A subtle, white opal shade encloses a cutting-edge LED light source that emanates soft, welcoming light as the day's rays begin to fade, helping you to extend your evening in comfort for as long as you desire.

Specifications:

- Black (-31) (painted)
- Steel Construction
- Frosted Glass bowl
- Eight expansive Black blades generate a cooling airflow as they are complemented by a handsome Black finish
- A subtle, white opal shade encloses a cutting-edge LED light source that provides soft, welcoming light along with energy- and cost-saving benefits
- Performs best in your favorite large living areas, such as a great room, living room, or covered outdoor space where the fan's beautiful blades can keep you cool and comfortable
- Effortlessly control the full range dimming and fan speed capabilities with a six-speed, full function remote control with its batteries included, making it ready for immediate use
- The light kit contains a frosted, white opal glass shade and is comprised of an 18w dimmable, 3000k LED module that offers a 1400 lumens source, 90+ CRI
- Measures 72 in dia, 16-3/4 in ht, and 80 in lead wires
- Includes a 3/4 in X 6 in down rod with the option to order longer accessory rods separately
- UL damp location listed
- Can be used to comply with California Title 20 or to comply with 2016 Title 24 JA8
- Mounting hardware and a limited lifetime warranty are included
- Dimmable to 10% brightness (See Dimming Notes)canopy covers a standard 4" octagonal recessed outlet box
- Mounting bracket for outlet box included
- 80" of wire supplied
- Meets California Title 24 JA8-2016

Performance:

Number of Modules	1
Input Power	18w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	1400/77.7 (LM-82)
CCT	3000 K
CRI	90+ CRI
FCC	FCC Title 47, Part 15, Class B
Min. Start Temp	-10 °C
Max. Operating Temp	30 °C
Warranty	Limited Lifetime warranty
Labels	UL Damp location listed Meets California Title 24 JA8-2016

P2550-3130K

Images:



Dimensions:

Diameter: 72"
 Length: 72"
 Height: 16-3/4"

Glass
 Width: 7-1/8"
 Height: 7-7/8"

P2550-3130K

Dimming Notes:

P2550 is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron - NTEVL-300

Lutron - DVELV-300P

Lutron-DVCL-253P

Lutron - Caseta Wireless

IDevices - IDEV009

Leviton – 6672

Leviton – 6674

Lutron - AYCL-153P

Lutron - TGCL-153-PH-WH

Lutron - AYLV-600P

Lutron - MAELV-601

Leviton -AWSMT-EAW

Lutron - N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.