

PFXC SERIES

Corrugated Water Heater Connectors



Product Features

- Stainless steel corrugated
- Kink resistant
- IAPMO listed
- NSF/ANSI 61 compliant
- AB 1953 Compliant
- ASME A112.18.6
- Max. pressure: 125 psi
- Working temperature: 40°F – 160°F
- Max. temperature: 180°F
- Built-in dielectric sleeve to prevent possible galvanic corrosion
- 100% leak tested



PFXCHF18N

Materials

- Tubing: Stainless steel 304 (ASTM A240)
- Nut: Chrome plated brass 3771
- Gasket: High-quality EPDM

Product Specifications

Model Number	Description	Length (in)	Length (mm)
PFXCHF18N	LF 3/4 FIPXPUSH 18 SS COR WHTR CONN	18"	457.2mm
PFXCHFT18N	LF 3/4 FIP 18 SS COR WHTR CONN	18"	457.2mm
PFXCHFT24N	LF 3/4 FIP 24 SS COR WHTR CONN	24"	609.6mm
PFXCHGT18	LF 1 FIP 18 SS COR WHTR CONN	18"	457.2mm
PFXCHGT24	LF 1 FIP 24 SS COR WHTR CONN	24"	609.6mm
PFXCHHT18	LF 1-1/4 FIP 18 SS COR WHTR CONN	18"	457.2mm
PFXCHJT18	LF 1-1/2 FIP 18 SS COR WHTR CONN	18"	457.2mm
PFXCHGFT24N	LF 1X3/4 FIP 24 SS COR WHTR CONN	24"	609.6mm
PFXCHHGT24	LF 1-1/4X1 FIP 24 SS COR WHTR CONN	24"	609.6mm
PFXCHFM18N	LF 3/4 MXF 18 SS COR WHTR CONN	18"	457.2mm
PFXCHFM24N	LF 3/4 MXF 24 SS COR WHTR CONN	24"	609.6mm
PFXCHFW18NA	LF 3/4 FIPXSWT 18 SS COR WHTR CONN	18"	457.2mm
PFXCHFW24NA	LF 3/4 FIPXSWT 24 SS COR WHTR CONN	24"	609.6mm

Warranty and Codes

These PROFLO products carry a 1-year limited warranty.

