

# LED ALABASTER

Project:

Fixture Type: Location:

Contact:

Ceiling mounted • Damp location listed

Images:



# **Description:**

One-light LED Flush Mount series featuring an etched Alabaster glass bowl. Fixtures are dimmable to 10% with Triac, phase forward or ELV dimmers.

# **Specifications:**

Antique Bronze (-020) (painted) Steel construction Etched Alabaster glass bowl Dimmable (See Dimming Notes) Unit covers a standard 4" hexagonal recessed outlet box Mounting strap for outlet box included 6" of wire supplied ENERGY STAR® qualified

#### **Performance:**

Number of Modules	1
Input Power	30w
Input Voltage	120 V
Input Frequency	50/60 Hz
Lumens/LPW	2622/88 (LM-82)
ССТ	3000 K
CRI	90+
Life (hours)	54,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-25 °C
Max. Operating Temp	25 °C
Warranty	5 year warranty
Labels	ETL Damp location listed
	ENERGY STAR <sup>®</sup> qualified



P350004-020-30

#### **Dimensions:**

Diameter: 19" Height: 8-3/4"





# LED ALABASTER

Ceiling mounted • Damp location listed



# P350004-020-30

### **Dimming Notes:**

P350004-020-30 is designed to be compatible with many Triac/Forward Phase or Reverse Phase (ELV) controls.

The following is a partial list of known compatible dimmer controls.

### **Dimming Controls**

Lutron NTELV-300	
Leviton 6681	
Leviton 6672	
Leviton 6674	
Lutron AYCL-153P	
Lutron AYLV-600P	
Lutron NTLV-600	
Lutron MAELV-601	
Leviton AWRMG-EAW	
Lutron N-600	

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.