

Specifications:

One-light LED Flush Mount (11")

Description:

Construction:

LED SQUARE

Project:

Fixture Type: Location:

Contact:

Ceiling mounted • Damp location listed



P350020-009-30

Images:



Dimensions:

Square: 11-3/8" Height: 5"

Brushed Nickel (-009) Steel construction Glass: Etched Alabaster glass bowl Flicker-free dimming to 10% brightness with most ELV type dimmers (See Dimming Notes) Unit covers a standard 4" hexagonal recessed outlet box Mounting strap for outlet box included 6" of wire supplied Brushed Nickel finish 120V AC replaceable module Dimmable to 10% with Triac or ELV dimmers 3000k color temperature TM-21 60,000 hour life

Performance:

Number of Modules	1		
Input Power	24W		
Input Voltage	120V		
Input Frequency	60Hz		
Lumens/LPW	2015/83.9 (LM-79) per module		
ССТ	3000K		
CRI	90+		
Life	60,000 (L70/TM-21)		
EMI/RFI	FCC Title 47, Part 15, Class B		
Min. Start Temp	-30° C		
Max. Operating Temp	30° C		
Warranty	5 year warranty		
Labels	cCSAus Damp location listed		
	ENERGY STAR [®] qualified		

Catalog number:

Base		Finish	,	Color Temp	CRI
P350020	•	009 - Brushed Nickel	- /	30	Blank- 90 CRI

For more information visit our website: www.progresslighting.com