

Project:		
Fixture Type:		
Location:		
Contact:		

LED ALABASTER

Ceiling mounted · Damp location listed





Description:

One-light LED Flush Mount series featuring an etched Alabaster glass bowl. Fixtures are dimmable to 10% with Triac, phase forward or ELV dimmers.

Specifications:

Antique Bronze (-020) (painted)
Steel construction
Etched Alabaster glass bowl
Dimmable (See Dimming Notes)
Unit covers a standard 4" hexagonal recessed outlet box
Mounting strap for outlet box included
6" of wire supplied
ENERGY STAR® qualified

Performance:

Number of Modules	1	
Input Power	21w	
Input Voltage	120 V	
Input Frequency	50/60 Hz	
Lumens/LPW	1601/81 (LM-82)	
CCT	3000 K	
CRI	90+	
Life (hours)	54,000 (L70/TM-21)	
EMI/RFI	FCC Title 47, Part 15, Class B	
Min. Start Temp	-25 °C	
Max. Operating Temp	25 °C	
Warranty	5 year warranty	
Labels	ETL Damp location listed	
	ENERGY STAR® qualified	

P350001-020-30

Images:



Dimensions:

Diameter: 11" Height: 5-1/2"





LED ALABASTER

Ceiling mounted · Damp location listed



P350001-020-30

Dimming Notes:

P350001-020-30 is designed to be compatible with many Triac/Forward Phase or Reverse Phase (ELV) controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron NTELV-300

Leviton 6672

Leviton 6674

Lutron AYLV-600P

Lutron NTLV-600

Lutron MAELV-600

Lutron N-600

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.