

# LED LINEN

Project:

Fixture Type: Location:

Contact:

Ceiling mounted • Damp location listed

Images:



# **Description:**

One-light LED Flush Mount series featuring an etched white linen glass bowl. Fixtures are dimmable to 10% with Triac, phase forward or ELV dimmers.

# **Specifications:**

Antique Bronze (-020) (painted) Steel construction Etched White Linen glass bowl Dimmable (See Dimming Notes) Unit covers a standard 4" hexagonal recessed outlet box Mounting strap for outlet box included 6" of wire supplied ENERGY STAR® qualified

### **Performance:**

1 21w
21w
120 V
50/60 Hz
1716/88 (LM-82)
3000 K
90
54,000 (L70/TM-21)
FCC Title 47, Part 15, Class B
-25 °C
25 °C
5 year warranty
ETL Damp location listed
ENERGY STAR <sup>®</sup> qualified





#### **Dimensions:**

Diameter: 13" Height: 5-3/8"

Ing facts	g+a
t (Lumens) 115	52
20.1 Watt (Efficacy) 57.1	1.5
acy Idex (CRI) 9	90
persidue (CCT) 3000 (Bright White	,)
Bright White Daylight	
K 4800K 650 pto ESNA UK-79-2008. Approved Method for the Electrical am product State Lighting. The U.E. Department of Energy (DOE) we readle.	d.
ngfacts.com for the Label Reference Guide.	
H64-HE7X81 (8:13:2016) № 620-30	



# LED LINEN

Ceiling mounted • Damp location listed



# P350006-020-30

### **Dimming Notes:**

P350006-020-30 is designed to be compatible with many Triac/Forward Phase or Reverse Phase (ELV) controls.

The following is a partial list of known compatible dimmer controls.

## **Dimming Controls**

Lutron NTELV-3	00		
Leviton 6672			
Leviton 6674			
Lutron AYLV-60	OP		
Lutron NTLV-60	00		
Lutron MAELV-	500		
Lutron N-600			

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.