

Project:	
Fixture Type:	
ixture type.	
_ocation:	
Contact:	

LED SQUARE

Ceiling mounted · Damp location listed

PROGRESS	S LE	D)



Specifications:

Description:

One-light LED Flush Mount (11")

Construction:

Brushed Nickel (-009) Steel construction

Glass: Random Swirl glass bowl

Flicker-free dimming to 10% brightness with most ELV type dimmers

(See Dimming Notes)

Unit covers a standard 4" hexagonal recessed outlet box

Mounting strap for outlet box included

6" of wire supplied

Brushed Nickel finish

120V AC replaceable module

Dimmable to 10% with Triac or ELV dimmers

3000k color temperature

TM-21 60,000 hour life

Performance:

Number of Modules	1
Input Power	24W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	2015/83.9 (LM-79) per module
CCT	3000K
CRI	90+
Life	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	cCSAus Damp location listed
	ENERGY STAR® qualified

P350018-009-30

Images:



Dimensions:

Square: 11-3/8" Height: 5"

Catalog number:

 Base
 Finish
 /
 Color Temp
 CRI

 P350018
 009 - Brushed Nickel
 /
 30
 Blank- 90 CRI