

LED ALABASTER

Ceiling mounted • Damp location listed



Description:

One-light LED Flush Mount series featuring an etched Alabaster glass bowl. Fixtures are dimmable to 10% with Triac, phase forward or ELV dimmers.

Specifications:

Brushed Nickel (-009) (plated)
Steel construction
Etched Alabaster glass bowl
Dimmable (See Dimming Notes)
Unit covers a standard 4" hexagonal recessed outlet box
Mounting strap for outlet box included
6" of wire supplied
ENERGY STAR® qualified

Performance:

Number of Modules	1
Input Power	21w
Input Voltage	120 V
Input Frequency	50/60 Hz
Lumens/LPW	1716/88 (LM-82)
CCT	3000 K
CRI	90+
Life (hours)	54,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-25 °C
Max. Operating Temp	25 °C
Warranty	5 year warranty
Labels	ETL Damp location listed ENERGY STAR® qualified

P350002-009-30

Images:



Dimensions:

Diameter: 13"
Height: 6-1/2"



LED ALABASTER

Ceiling mounted • Damp location listed



P350002-009-30

Dimming Notes:

P350002-009-30 is designed to be compatible with many Triac/Forward Phase or Reverse Phase (ELV) controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron NTELV-300

Leviton 6672

Leviton 6674

Lutron AYLV-600P

Lutron NTLV-600

Lutron MAELV-600

Lutron N-600

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.
Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.