# 4U Series 120V Xenon Collection 8" Xenon Harmonization 120V Cabinet Light -BZT

4U120X08BZT



### **Dimensions**

| Height | 1.25" |
|--------|-------|
| Length | 8.00" |
| Width  | 4.50" |

| Project Name: |  |
|---------------|--|
| Location:     |  |
| Туре:         |  |
| Qty:          |  |
| Comments:     |  |

## **Ordering Information**

| Product ID         | 4U120X08BZT                        |
|--------------------|------------------------------------|
| Available Finishes | BZT, NIT, WHT                      |
| Collection         | 4U Series 120V Xenon<br>Collection |

### **Dimensions**

| Weight   | 0.75 LBS |
|----------|----------|
| VVCIGITE | 0.75 LDO |

## **Specifications**

| Material          | Aluminum |
|-------------------|----------|
| Glass Description | Frosted  |

#### **Electrical**

| Yes                |
|--------------------|
| 108-132V           |
| Single(120)        |
| 108-132V           |
| Hi-Low-Off, Rocker |
|                    |

### Qualifications

| Safety Rated       | Dry                      |
|--------------------|--------------------------|
| Expected Life Span | 2500 Hours               |
| Warranty           | www.kichler.com/warranty |

### Installation

| Wire Connectors     | Wire Nuts |
|---------------------|-----------|
| Direct Wire         | Yes       |
| Knockouts           | 0.5 in    |
| Number of Knockouts | 4         |
| Modular             | Yes       |

## **Primary Lamping**

| Light Source          | Incandescent |
|-----------------------|--------------|
| Lamp Included         | Included     |
| Number of Lights/LEDs | 1            |
| Max or Nominal Watt   | 20W          |
| Socket Type           | Bi-Pin       |
| Lamp Type             | G8           |
| Bulb Product ID       | 12090CLR     |
| Dimming               | Yes          |



7711 East Pleasant Valley Road Cleveland, Ohio 44131-8010 Toll free: 866.558.5706 or kichler.com

#### Notes

1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.



