


Reliant 3®



TU385502WDXH Bath/Shower Trim Shown

GENERAL DESCRIPTION:

Double Ceramic Pressure Balance Cartridge: Features one-piece design with ceramic discs and ceramic balancing spool. Includes integrated check valves and hot limit safety stop. Cartridge available for back to back capability. Ceramic balancing spool maintains constant output temperature in response to changes in relative hot and cold supply pressure. Washerless ceramic discs provide smooth handle movement and are unaffected by harsh water conditions.

Trim: Features metal slip-on diverter spout. Metal wall valve trim with metal lever with RED/BLUE indicator ring.

PRODUCT FEATURES

One-Piece Cartridge: Simplifies installation and maintenance.

Double Ceramic Pressure Balance Cartridge:

Combination of Ceramic Disc Mixing Valve and a Ceramic Balancing Spool in a one-piece cartridge.

Ceramic Disc Mixing Valve: Assures a lifetime of drip-free performance and smooth handle operation.

Ceramic Balancing Spool: Maintains a constant output temperature in response to changes in relative hot and cold supply pressure. Ceramic material is unaffected by mineral deposits and harsh water conditions.

Integrated Check Valves: Engineered to eliminate cross flow. **Adjustable Hot Limit Safety Stop:** Limits the amount of hot water allowed to mix with cold. Reduces the risk of accidental scalding.

Comfort Zone: Offers a wider shower range to fine tune the desired temperature within the useful temperature zone.

Back-to-Back Capability: Hot and cold can be reversed quickly and easily.

SUGGESTED SPECIFICATION

Bath/shower fitting shall feature double ceramic pressure balance cartridge. Cartridge shall feature integrated check valves to eliminate cross flow. Capable of meeting ASSE1016 @1.3gpm. Cartridge shall also feature hot limit safety stop. Fitting shall be: American Standard - Trim Kit Model # TU38550_WDXH.___ and Flash Valve Body Model # RU10___.


Pressure Balance Bath/Shower Trim with Double Ceramic Pressure Balance Cartridge

MODEL NUMBER:

TRIM KITS:

- TU385502WDXH Reliant 3 Bath/Shower Trim Kit with Pressure Balance Cartridge LESS showerhead. Lever handle. LESS valve body with RED/BLUE indicator ring.
- □ TU385501WDXH Reliant 3 Shower ONLY Trim Kit with Pressure Balance Cartridge Lever handle. LESS valve body with RED/BLUE indicator ring.

For use with Flash[™] Rough Valve Bodies






Reliant 3[®] **Pressure Balance Bath/Shower Trim** with Double Ceramic Pressure Balance Cartridge

CODES AND STANDARDS

These products meet or exceed the following codes and standards:

ASSE 1016 / ASME A112.18.1016 / CSA B125.16 ASME A112.18.1 / CSA B125.1 Rated to meet ASSE 1016 @ 1.3gpm



TRIM KITS *			Finish Options	
	Product		Polished Chrome	PVD Brushed Nickel
	Number	Description	002	295
	TU385502WDXH	Bath/Shower trim kit with RED/BLUE indicator ring. Metal lever handle. LESS showerhead. LESS valve body.		
	TU385501WDXH	Shower only trim kit with RED/BLUE indicator ring. Metal lever handle.		

* TRIM & ROUGH MUST BE ORDERED SEPARATELY.

DIES	Product Description	Without Screwdriver Stops	With Screwdriver Stops
Flash [™] ROUGH VALVE BO	Rough Valve Body. Universal* inlets/outlets.	RU101	RU101SS
	Rough Valve Body. Stub-out inlets/outlets for Press-Fit Fittings.	RU102	RU102SS
	Rough Valve Body. PEX inlets/Universal outlets for Crimp Ring PEX system (ASTM F1807).	RU107	RU107SS
	Rough Valve Body. PEX Elbow inlets/Universal outlets for Crimp Ring PEX system (ASTM F1807).	RU107E	RU107ESS
	Rough Valve Body. PEX inlets/Universal outlets for Cold Expansion PEX system (ASTM F1960).	RU108	RU108SS
	Rough Valve Body. PEX Elbow inlets/Universal outlets for Cold Expansion PEX system (ASTM F1960).	RU108E	RU108ESS
	Rough Valve Body. CPVC inlets/Universal outlets.	RU109	RU109SS

ONAL SSORY	Product Number M954805-0070A	Product Description
OPTI	M954805-0070A	Deep Rough-In Kit
•	M970640-0070A	Back to Back Cartridge

ÁDA P

Meets the American Disabilities Act Guidelines and **ANSI A117.1** Requirements for the physically challenged.