

see what Delta can do<sup>SM</sup>

## AIR GAP

### STANDARD SPECIFICATIONS:


- To prevent backflow or back siphonage of non potable water into potable water systems.
- Deck mount only
- Deck thickness 0" (0 mm) min. to 1 1/2" (39 mm) max.
- 1 1/4" (32 mm) minimum to 1 5/8" (41 mm) max. mounting hole required.
- 5/8" O.D. inlet x 7/8" O.D. outlet
- Molded polypropylene
- Nitrile rubber washer

### WARRANTY

- Parts and Finish – Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.).
- Please go to [www.deltafaucet.com](http://www.deltafaucet.com) for the complete details of our limited warranty.

### COMPLIES WITH:

- IAPMO PS 23



▲ Designate Proper Finish Suffix

Delta Faucet Company reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or [www.deltafaucet.com](http://www.deltafaucet.com) for finish options and product availability.

**Delta Faucet Company**  
 55 E. 111th Street, Carmel, IN 46280  
 350 South Edgeware Road, St. Thomas, ON N5P 4L1  
 © 2025 Delta Faucet Company