



▲ Designate proper finish suffix



see what Delta can do



- 2-In-1 Shower
- 5-Spray Setting Hand Shower

FEATURES:

- Touch-Clean[®] Spray Holes
 MagnaTite[®] Docking
- ProClean™ Spray Setting

STANDARD SPECIFICATIONS:

- Max flow rate 1.75 gpm at 80 psi, 6.6 L/min @ 550 kPa (58596-▲-PK)
- Max flow rate 2.5 gpm at 80 psi, 9.5 L/min @ 550 kPa (58596-▲25-PK)
- Integrated hand shower docks securely into shower head when not in use
- · 3-Way diverter allows for single or shared operation of shower head and hand shower
- Change hand shower spray modes with push button pause in handle – pause is a non-positive shut-off
- 60"~82" (1524~2083 mm) stretchable metal hose
- Ball connector swivel angle is 32° (16° per side)
- Fits standard 1/2"-14 NPT pipe fitting
- 5 Spray settings include: Full body spray, Massage spray, Full w/ massage spray, ProClean™ spray and Pause

WARRANTY

- Parts and Finish Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.).
- Please go to www.deltafaucet.com for the complete details of our limited warranty.



COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1◆
- ASME A112.18. 3◆
 EPA WaterSense® Applies to 58596-▲-PK only
- ◆Your Delta hand shower incorporates a backflow protection system that has been tested to be in compliance with ASME A112.18.3 and ASME A112.18.1/CSA B125.1. It incorporates two certified check valves in series, which operate independently and are integral, non-serviceable parts of the wand assembly.

Delta Faucet Company 55 E. 111th Street, Carmel, IN 46280 350 South Edgeware Road, St. Thomas, ON N5P 4L1 © 2025 Delta Faucet Company