



▲ Designate proper finish suffix



see what Delta can do™

IN2ITION®

■ 2-In-1 Shower

■ 5-Spray Setting Hand Shower

FEATURES:

- Touch-Clean® Spray Holes
- MagnaTite® Docking

STANDARD SPECIFICATIONS:

- Max flow rate 1.75 gpm @ 80 psi, 6.6 L/min @ 550 kPa
- Hand shower with five spray settings - pause is a non-positive shut-off
- Integrated hand shower docks securely into shower head when not in use
- 3-Way diverter allows for single or shared operation of shower head and hand shower
- Fixed shower head and hand shower all in one
- Push-button activates pause mode. Lever changes spray settings.
- 72" (1829 mm) metal hose (Chrome and SN finishes only)
- 72" (1829 mm) UltraFlex hose (RB finish only)
- 5 Spray settings include: Full Body spray, Fast Massage spray, Full Spray with Massage, Slow Massage spray and Pause

WARRANTY:

- Parts and Finish – Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.).
- Please go to www.deltafaucet.com for the complete details of our limited warranty.



COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- EPA WaterSense®

Delta Faucet Company reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.

DSP-B-75595C Rev. C

Delta Faucet Company

55 E. 111th Street, Carmel, IN 46280
350 South Edgeware Road, St. Thomas, ON N5P 4L1
© 2025 Delta Faucet Company