

75756▲



see what Delta can do™

HAND SHOWER/ SHOWER HEAD COMBO

- 4-Spray Setting Shower Head
- 5-Spray Setting Hand Shower

FEATURES:

- Touch-Clean® Spray Holes

STANDARD SPECIFICATIONS:

- Max flow rate 1.75 gpm @ 80 psi, 6.6 L/min @ 550 kPa
- Hand shower with 5-spray settings; Full Spray, Shampoo Spray, Massage Spray, Full Spray w/Massage, and Pause. Pause is a non-positive shut-off.
- Shower head with 4-spray settings; Full Spray, Massage Spray, Full Spray w/Massage, and Pause. Pause is a non-positive shut-off.
- Model includes 3-way diverter shower arm mount
- 3-way diverter allows for single or shared operation of shower head and hand shower
- Adjustable shower arm mounting for hands-free showering
- 60" (1524 mm) stainless steel hose (BL finish uses UF (Ultraflex) plastic hose)
- Standard 1/2"-14 NPT pipe fitting


WARRANTY

- Parts and Finish - Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.).
- Please go to www.deltafaucet.com for the complete details of our limited warranty.



COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- EPA WaterSense®



▲ Designate proper finish suffix

Delta Faucet Company reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.

DSP-B-75756 Rev. A

Delta Faucet Company
55 E. 111th Street, Carmel, IN 46280
350 South Edgeware Road, St. Thomas, ON N5P 4L1
© 2025 Delta Faucet Company