



▲ Designate Proper Finish Suffix



see what Delta can do

FLOOR MOUNT TUB FILLER

 Coordinates with Trinsic[®] Bath Collection

STANDARD SPECIFICATIONS:

- Hand shower max flow rate 1.75 gpm @ 80 psi, 6.6 L/min @ 550 kPa
- Spout flow up to 10 gpm @ 60 psi, 37.8 L/min @ 410 kPa
- Hot and cold indicators
- Swing spout
- 60"-82" stretchable hose with metal fittings
- · Auto resetting diverter
- Dual integral check valves in hand shower
- Optional pressure balanced cartridge (RP46074) available
- · Pivot hand shower holder
- Must order R4700-FL or R4700-FLWS

WARRANTY

- Parts and Finish Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.).
- Electronic Parts and Batteries (if applicable) 5 years from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.); or for commercial purchasers, 1 year from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.). No warranty is provided on batteries.
- Please go to www.deltafaucet.com for the complete details of our limited warranty.

WARNING: Risk of personal injury. Do not use the tub filler as a grab bar or support bar. Install this product according to the installation guide.



COMPLIES WITH:

- ASME A112.18.1/ CSA B125.1 L ICC/ANSI A117.1 - Valve control only
- EPA WaterSense®

Delta Faucet Company

55 E. I I I I th Street, Carmel, IN 46280 350 South Edgeware Road, St. Thomas, ON N5P 4L I © 2024 Delta Faucet Company