

PRODUCT SPECIFICATIONS

Lustertone® Stainless Steel Single Bowl Top Mount Sink. Overall dimensions are 25" x 22" x 5". Sink is manufactured from 18 gauge 304 Stainless Steel with a Lustrous Highlighted Satin finish, Rear Center drain placement and Full spray sides and bottom.

| Installation Type: | Top Mount |
|-----------------------|-------------------------------------|
| Material: | 304 Stainless Steel |
| Finish: | Lustrous Highlighted Satin |
| Gauge: | 18 |
| Sound Deadening: | Full spray sides and bottom |
| Number of Bowls: | 1 |
| Sink Dimensions: | 25" x 22" x 5" |
| Bowl 1 Dimensions: | 16" x 19" x 4-7/8" |
| Drain Size: | 3-1/2" (89mm) |
| Drain Location: | Rear Center |
| Minimum Cabinet Size: | 30" |
| Mounting Hardware: | Part # 64090012 included for |
| | countertops up to 3/4" (19mm) thick |
| Cutout Template #: | <u>1000001188</u> |

Template is available for download at elkay.com

Cutout Dimensions for Top Mount Installation:


24-3/8" x 21-3/8" (619mm x 543mm) with 1-1/2" (38mm) corner radius




This sink is compliant to ADA and ANSI/ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards.

Hole Drilling Configurations:

1-1/2" (38mm) Diameter Faucet Holes on 4" (102mm) Centers 1-1/8" (29mm) Diameter Slotted Hole







AMERICAN PRIDE. A LIFETIME TRADITION. Like your family, the Elkay family has values and traditions that endure. For almost a century, Elkay has been a family-owned and operated company, providing thousands of jobs that support our families and communities.






Sinks are listed by IAPMO[®] as meeting the applicable requirements of the Uniform Plumbing Code[®], International Plumbing Code[®], and National Plumbing Code of Canada.

Product Compliance:

ADA BUY AMERICAN ACT ASME A112.19.3/CSA B45.4

<u>Clean and Care Manual (PDF)</u> Installation Instructions (PDF) Limited Lifetime Warranty (PDF)

Similar models are available with: Quick-Clip Mounting System, additional ADA depths




In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.

APPROVAL:



Installation Profile:



OPTIONAL ACCESSORIES

| Hardware: | LK364, LK463 |
|-----------|---------------------|
| Sinkmate: | LKSM17, LKSMHOOK, |
| | LKSMSPONGE, LKSMHSL |

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.