### Slimline Soft Sides® Fountain Non-Filtered Non-Refrigerated Freeze Resistant Stainless Steel

### Model ECDFPW314FPK

#### PRODUCT SPECIFICATIONS

Slimline Soft Sides® Fountain Non-Filtered Non-Refrigerated Freeze Resistant Stainless Steel, Features shall include Freeze Resistant. Furnished with Vandal Resistant bubbler. Mechanical Front Bubbler Button activation. Product shall be Wall Mount (On Wall), for Indoor + Outdoor applications, serving 1 station(s).

Special Features:	Freeze Resistant	
Finish:	Stainless Steel	
Power:	No Electrical Required	
Bubbler Style:	Vandal Resistant	
Activation by:	Mechanical Front Bubbler Button	
Mounting Type:	Wall Mount (On Wall)	
Chilling Capacity:	Non-refrigerated	
Dimensions (L x W x H):	19-3/4" x 19-3/8" x 20-3/8"	
Approx. Shipping Weight:	41 lbs.	
Installation Location:	Indoor + Outdoor	
No. of Stations Served:	1	

\*\*When used in non-temperature controlled environments, unit(s) must be adequately winterized and/or protected from extreme heat to prevent damage where climates dictate.

- Mechanically-Activated unit continues to supply water in event of service disruptions.
- Freeze Resistant:
  - Depending on specific installation, freeze resistant system is located either below frost line or in temperature controlled space.



Included with Product:

Fountain. Freeze Resistant Box

#### ▼ Ships in multiple boxes

A Century of Tradition and Quality. For more than 100 years, Elkay has been making innovative products and providing exceptional customer care. We take pride in offering plumbing products that make life easier, inspire change and leave the world a better place.



#### PRODUCT COMPLIANCE

ADA & ICC A117.1 ASME A112.19.3/CSA B45.4 NSF/ANSI 61 (Q≤1) & 372 (lead free)





Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards. Installation may require additional components and/or construction features to be fully compliant. Consult the local Authority Having Jurisdiction if necessary.

Installation Instructions (PDF) - 98011C Installation Instructions (PDF) - 97566C

Water Systems are warranted for 12 months from date of installation. Warranty pertains to drinking water applications only. Nondrinking water applications are not covered under warranty. Warranty (PDF)

PART:	QTY:
PROJECT:	
CONTACT:	
NOTES:	
APPROVAL:	

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.

## Slimline Soft Sides® Fountain Non-Filtered Non-Refrigerated Freeze Resistant Stainless Steel

# Model ECDFPW314FPK

Optional Accessories		
<u>EWF172</u>	Universal Filtration Kit (1500-Gallon)  Spec Sheet (PDF)	(In)
<u>AP99</u>	Access Panel 9" x 9" x 6"  Spec Sheet (PDF)	
<u>98481C</u>	Bubbler Kit Water-Efficient Vandal-Resistant  Spec Sheet (PDF)	
LKAPR2	Cane Apron for EHW Stainless Steel  Spec Sheet (PDF)	4


In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.




**INSTALLER NOTE** 

This drinking fountain is furnished with a bubbler and valve including all connecting fittings which are manufactured of completely lead free material. Shut off valve (not furnished) to accept 3/8" O.D. unplated copper tube.

**WARNING:** The freeze-resistant box must be installed on an interior heated wall where the temperature does not drop below 50°F (10°). The dront of the box must have unobstructed air flow. Failure to maintain the interior wall temperature and the inside of the freeze-resistant box above 50°F (10°) can result in damage to the box which could result in unrestricted water flow.



In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.



\*Child ADA Requirement

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.