Rowan Chandelier

GENERATION LIGHTING CHANDELIER

GENERAL PRODUCT INFORMATION:

These fixtures are intended to be installed utilizing NEC compliant junction boxes.

This product is safety listed for damp locations.


This instruction shows a typical installation.

CAUTION - RISK OF FIRE

This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.

Use minimum 90°c supply conductors.


SAVE THESE INSTRUCTIONS!



GENERATION LIGHTING 7400 Linder Ave., Skokie, IL 60077 T 847.410.4400 | F 847.410.4500 www.generationlighting.com



Install the Fixture



Screw the half ball to the stem which will be on top.

2 Determine the wanted height or look of the fixture with the provided stems, then assemble them by screwing them together.

- 3 Feed the fixture wires through the stem assembly, then screw the stem assembly on top of the fixture.
- 4 Feed the fixture wires through the collar nut, canopy, and the half ball assembly, then screw it onto the stem assembly.
- 5 Spread the arms evenly and place the steel ring from the top of the fixture onto the arms.
- 6 Align and secure the mounting plate to the junction box, then slide the half ball assembly onto the mounting plate.
- 7 Connect the fixture to a suitable ground in accordance with local electrical codes.
- 8 Connect the white fixture wire to the neutral power line wire with a wire nut.
- 9 Connect the black fixture wire to the hot power line wire with a wire nut.
- Neatly place all the wires into the junction box, place the canopy onto the mounting plate, and secure it in place by screwing the collar nut tightly onto the mounting plate.
- Screw the lamps into the sockets. Refer to the label on the socket for Max Wattage Information.
- Place the shade into the shade base and secure in place with the thumb screws (do not over tighten). Repeat for remaining shades.