## 101899

### **CUBEO**

# SINGLE HOLE SINGLE HANDLE S-SIZE BATHROOM FAUCET, LESS DRAIN, 1.2 GPM (4.5L/MIN)

# ZE





- GROHE StarLight® maintains luster on brushed and polished finishes
- GROHE Silkmove® Durable ceramic cartridge features a ceramic disc mixing valve and a ceramic balancing spool
- GROHE EcoJoy® uses less water without sacrificing performance
- Faucet Height: 5-7/8"
- Spout Reach: 4-3/16"
- Aerator Height: 3-3/8"
- · Metal body and handle
- 1.2 gpm (4.5 L/min) meets WaterSense Requirements
- Can handle Thermal Disinfection cycle of 82C for 30 minutes
- · Supply lines included, Excludes drain



#### **PRODUCT FEATURES:**



GROHE SilkMove®

GROHE EcoJoy®

#### **CERTIFICATIONS:**

- IAPMO (cUPC)
- EPA Watersense
- State of Massachusetts

#### **COMPLIES WITH:**

- ASME A112.18.1/CSA B125.1
- NSF/ANSI/CAN 61
- NSF/ANSI/CAN 372

#### **AVAILABLE FINISHES:**

1018990000 CHROME

**1018992430** MATTE BLACK

101899EN00 BRUSHED NICKEL

101899GN00 BRUSHED COOL SUNRISE

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations. We reserve the right to make revisions without notice to product specifications. 1-15-2025



## 101899

## **CUBEO**



# SINGLE HOLE SINGLE HANDLE S-SIZE BATHROOM FAUCET, LESS DRAIN, 1.2 GPM (4.5L/MIN)

#### **TECHNICAL DATA:**

Product Height 7-3/16 in

Product Length 4-3/16 in

Product Width 1-7/8 in

Fitting Spout Height 3-3/8 in

Fitting Spout Reach 5 in

Fitting Handle Height 5-7/8 in

GPM (Min)-GPM (Max) 1.2 gal (US)/min

1

Fitting No of Holes Required

7<sup>3</sup>/<sub>16</sub>° 5<sup>7</sup>/<sub>2</sub>° Ø1<sup>7</sup>/<sub>8</sub>° (Ø48) 17° 3<sup>3</sup>/<sub>8</sub>° (Ø34) 21<sup>5</sup>/<sub>16</sub>° (Ø34) 21<sup>5</sup>/<sub>16</sub>° (Ø34) 3<sup>3</sup>/<sub>8</sub>° comp. (<sup>3</sup>/<sub>16</sub>° -24 UNEF) 50°