


design • illuminate • enjoy

## assembly instructions

Family: Martina | Item No. 4457 GR




## **Drawing 1 - Strap Detail**





- 1. Find a clear area in which you can work.
- 2. Unpack fixture and glass from carton.
- 3. Carefully review instructions prior to assembly.

## **Drawing 2 - Fixture Mounting**



\*\*\* The construction of this fixture will be accomplished by first determining the length of stem required, mounting the attaching strap to the junction box, making all necessary elctrical connections, hanging the fixture from the ceiling, and then installing the glass.

- 1. Determine the overall length you will need the assembled fixture to be.
  - 2. Determine what stems will be needed to achieve the overall length you require. (Additional stems are available and can be ordered. Ask your local Hinkley Lighting representative or visit www.hinkleylighting.com for information.)
  - 3. Install stems by slipping them onto the supply wire of the fixture, threaded end up, and threading them together.

## **Drawing 3 - Glass Installation**



- 1. Prepare gem strap (A) for mounting by threading two screws (B) provided into back of gull wing bracket of gem strap (A) - see Drawing 1.
- Be sure the holes into which the screws are threaded match the spacing of holes (D) in the canopy (E) - see Drawings 1 and 2.
- 3. Mount gem strap (A) to junction box (J), using the two 1" screws (C) provided.

**SAFETY WARNING: READ WIRING AND GROUNDING INSTRUCTIONS (I.S. 18)** AND ANY ADDITIONAL DIRECTIONS. TURN POWER SUPPLY OFF DURING INSTALLATION. IF NEW WIRING IS REQUIRED, CONSULT A QUALIFIED **ELECTRICIAN OR LOCAL AUTHORITIES FOR CODE REQUIREMENTS.** 

- Make electrical connections from supply wire to fixture lead wires. Refer to instruction sheet (I.S. 18) and follow all instructions to make all necessary wiring connections. Then refer back to this sheet to continue installation of this fixture.
  - 1. Hang the fixture by slipping the holes (D) in the canopy, over the screws (B) in the mounting strap - see Drawing 2.
    - 2. Thread on ball knobs (F) to secure fixture to the ceiling.
  - 1. To install glass, remove socket ring (3) from socket (1) see Drawing 3.
    - 2. Slip glass (2) over socket (1) and thread socket ring (3) back on to socket (1) and tighten.
    - 3. Fixture can now be lamped accordingly.

Note: Maximum wattage for 4457 fixture is 100 watts per bulb.

3