

MR16 Well Light Textured Black

15092BKT (Textured Black)

Project Name: _____
Location: _____
Type: _____
Qty: _____
Comments: _____



Certifications/Qualifications

Location Rating UL_12V
www.kichler.com/warranty

Dimensions

Height 8.00"
Width 5.50"

Electrical

Operating Voltage Range 12 VAC
Voltage 12V

Mounting/Installation

Lead Wire Length 38

Primary Lamping

Lamp Included Not Included
Lamp Type MR16
Max or Nominal Watt 5.00

Product/Ordering Information

SKU 15092BKT
Finish Black
UPC 783927013673

Optional Lamping

2700K LED MR16 4W 15 Degree 18126
3000K LED MR16 4W 15 Degree 18127
2700K LED MR16 4W 25 Degree 18128
3000K LED MR16 4W 25 Degree 18129
2700K LED MR16 4W 40 Degree 18130
3000K LED MR16 4W 40 Degree 18131
2700K LED MR16 4W 60 Degree 18132
3000K LED MR16 4W 60 Degree 18133
2700K LED MR16 5W 15 Degree 18134
3000K LED MR16 5W 15 Degree 18135
2700K LED MR16 5W 25 Degree 18136
3000K LED MR16 5W 25 Degree 18137
2700K LED MR16 5W 40 Degree 18138
3000K LED MR16 5W 40 Degree 18139
2700K LED MR16 5W 60 Degree 18140
3000K LED MR16 5W 60 Degree 18141
2700K LED MR16 7W 15 Degree 18142
3000K LED MR16 7W 15 Degree 18143
2700K LED MR16 7W 25 Degree 18144
3000K LED MR16 7W 25 Degree 18145
2700K LED MR16 7W 40 Degree 18146
3000K LED MR16 7W 40 Degree 18147
2700K LED MR16 7W 60 Degree 18148
3000K LED MR16 7W 60 Degree 18149

Specifications

Material Aluminum & Polypropylene

Additional Finishes

Kichler

7711 East Pleasant Valley Road Cleveland, Ohio 44131-8010
Toll free: 866.558.5706 or kichler.com

Notes:

1) Information provided is subject to change without notice.
All values are design or typical values when measured under

KICHLER®

laboratory conditions.

2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.