

PHREE COLLECTION

Phree™ LED 56" Fan White

310175WH (White)



Project Name: _____
Location: _____
Type: _____
Qty: _____
Comments: _____

Airflow

| | |
|------------|------|
| CFM (High) | 6467 |
| CFM (Low) | 2574 |
| RPM (High) | 142 |
| RPM (Low) | 57 |

Certifications/Qualifications

| | |
|--------------------|--|
| Location Rating | Damp |
| Title 20 Compliant | Yes |
| | www.kichler.com/warranty |

Dimensions

| | |
|----------------|-----------------|
| Base Backplate | 6.75 DIA |
| Downrod 1 | 1.00 OD X 4.50" |
| Weight | 28.50 LBS |
| Height | 16.00" |
| Width | 56.00" |

Electrical

| | |
|-------------|--------------|
| Amps (High) | 0.73 |
| Amps (Low) | 0.33 |
| Motor Size | 188MM X 20MM |
| Motor Type | AC |

Mounting/Installation

| | |
|---|-----------|
| Minimum Distance from Fan to 7 feet Floor | |
| Interior/Exterior | Exterior |
| Lead Wire Length | 78 |
| Mounting Weight | 28.50 LBS |

Photometrics

| | |
|-----------------------|-------|
| Color Rendering Index | 80 |
| Kelvin Temperature | 3000K |

Primary Lamping

| | |
|-----------------------|------------|
| Downward-facing Bulbs | 1X17W |
| Dimmable | Yes |
| Downlight Included | Yes |
| Downlight Option | Integrated |
| Watts (High) | 87 |
| Watts (Low) | 18 |

Product/Ordering Information

| | |
|--------|--------------|
| SKU | 310175WH |
| Finish | White |
| Style | Contemporary |
| UPC | 783927542418 |

Specifications

| | |
|-----------------------|-------------------|
| Blade Finish 1 | WHITE |
| Blade Material | ABS |
| Blade Pitch | 22 |
| Blades Included | Yes |
| Blade Sweep | 56 |
| Diffuser Description | Etched Cased Opal |
| Material | ABS |
| Max Stem Tilt | 30 Degrees |
| Number of Blades | 3 |
| Wall Control Included | Yes |

Additional Finishes



Brushed Nickel



Walnut



White

Kichler

7711 East Pleasant Valley Road Cleveland, Ohio 44131-8010
Toll free: 866.558.5706 or kichler.com

Notes:

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

KICHLER®