

52" Basics Pro Premier Fan White

330016WH (White)

Project Name: _____
Location: _____
Type: _____
Qty: _____
Comments: _____



Airflow

CFM (High)	4200
CFM (Low)	1523
RPM (High)	161
RPM (Low)	57

Certifications/Qualifications

Location Rating	CSA UL Listed Dry
	www.kichler.com/warranty

Dimensions

Base Backplate	5.25 DIA
Downrod 1	1.00 OD X 4.00"
Downrod 2 - Measurement A	15.25"
Downrod 2 - Measurement B	7.50"
Downrod 2 - Measurement C	11.50"
Weight	22.58 LBS
Height	18.50"
Width	52.00"

Electrical

Amps (High)	0.43
Amps (Low)	0.07
Motor Size	153MM X 15MM
Motor Type	AC

Mounting/Installation

Minimum Distance from Fan to 7 feet Floor	
Interior/Exterior	Interior
Lead Wire Length	78
Low Ceiling Adaptable	Yes, Dual Mount Included
Mounting Weight	18.22 LBS

Photometrics

Color Rendering Index	80
Kelvin Temperature	3000K

Primary Lamping

Downward-facing Bulbs	4 X 4
Downlight Included	Yes
Downlight Option	Removable
Watts (High)	52
Watts (Low)	9

Product/Ordering Information


SKU	330016WH
Finish	White
Style	Traditional
UPC	783927572118


Specifications


Blade Finish 1	WHITE
Blade Finish 2	SILVER
Blade Material	WOOD
Blade Pitch	12
Blades Included	Yes
Blade Sweep	52
Diffuser Description	Etched Cased Opal
Material	STEEL


Max Stem Tilt	22 Degrees
Number of Blades	5
Blades Reversible	Yes


Additional Finishes


 Brushed Nickel


 Brushed Nickel

 Matte White

 Satin Black

 Satin Black

 Satin Natural Bronze

 White

Kichler

7711 East Pleasant Valley Road Cleveland, Ohio 44131-8010
Toll free: 866.558.5706 or kichler.com

Notes:

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

KICHLER®