

**Moderne Collection**  
**Moderne 1 Light Mini Pendant SN**  
42995SNLED (Satin Nickel)

Project Name: \_\_\_\_\_  
Location: \_\_\_\_\_  
Type: \_\_\_\_\_  
Qty: \_\_\_\_\_  
Comments: \_\_\_\_\_



### Dimensions

|                |         |
|----------------|---------|
| Height         | 12.00"  |
| Overall Height | 115.00" |
| Width          | 5.50"   |

### Ordering Information

|                    |                    |
|--------------------|--------------------|
| Product ID         | 42995SNLED         |
| Finish             | Satin Nickel       |
| Available Finishes | OZ, SN             |
| Collection         | Moderne Collection |

### Dimensions

|                |          |
|----------------|----------|
| Base Backplate | 6.50 DIA |
| Weight         | 4.00 LBS |

### Photometrics

|                       |       |
|-----------------------|-------|
| Kelvin Temperature    | 3000K |
| Color Rendering Index | 90    |

### Specifications

|          |       |
|----------|-------|
| Material | Steel |
|----------|-------|

### Electrical

|          |           |
|----------|-----------|
| Dimmable | Yes       |
| Voltage  | 120-277 V |

### Qualifications

|                    |                                                                        |
|--------------------|------------------------------------------------------------------------|
| Safety Rated       | Dry                                                                    |
| Expected Life Span | 40000 Hours                                                            |
| Warranty           | <a href="http://www.kichler.com/warranty">www.kichler.com/warranty</a> |

### Primary Lamping

|                        |            |
|------------------------|------------|
| Light Source           | LED        |
| Lamp Included          | Integrated |
| # of Bulbs/LED Modules | 2          |
| Delivered Lumens       | 800        |
| Delivered Efficacy     | 41         |
| Dimming                | Yes        |

**Notes:**

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.