

# KOHLER®

## Roughing-In

## K-3950 TRESHAM™ COMFORT HEIGHT® TOILET

### Product Information

|                         |                                |
|-------------------------|--------------------------------|
| Applicable product:     |                                |
| Comfort Height® toilet  | K-3950                         |
| Fixture:                |                                |
| Configuration           | two-piece, elongated           |
| Water per flush         | 1.28 gpf (4.8 lpf)             |
| Passageway              | 2-1/8" (54 mm)                 |
| Water area              | 11-1/2" (292 mm) x 9" (229 mm) |
| Water depth from rim    | 5-3/8" (137 mm)                |
| Seat post hole centers  | 5-1/2" (140 mm)                |
| Included components:    |                                |
| Bowl                    | K-4799                         |
| Tank                    | K-4899                         |
| Tank cover              | 1146775                        |
| Trip lever              | 1161319                        |
| Tank accessory pack     | 84581                          |
| Bolt cap accessory pack | 1013092                        |

#### Recommended accessories:

|   |        |
|---|--------|
| Angle supply with stop – 3/8" NPT                                       | K-7637 |
| Lustra™ elongated open-front toilet seat - for Accessibility compliance | K-4650 |
| Brevia™ elongated toilet seat   | K-9375 |

#### Optional accessories:

|                               |        |
|-------------------------------|--------|
| Left-hand trip lever (non-CP) | K-9375 |
|-------------------------------|--------|

### Installation Notes

Install this product according to the installation guide.

Will comply with the American Disabilities Act (**ADA**) when installed per the requirements of the Accessibility Guidelines, Section 604 Water Closets, of the Act, which include the installation of an open front seat.

Will comply with **CSA B651** when installed per Clause 4.3.6 of the standard.

Will comply with **OBC** Barrier Free requirements when installed per Clause 3.8.3.8 and 3.8.3.9.

Fixture conforms to ASME Standard A112.19.2/CSA B45.1. All dimensions are nominal.

