

PINOIR_®

Features

- Vitreous china
- Wall-mount
- With overflow
- 8" (20.3 cm) centers (-8), 4" (10.2 cm) centers (-4), or single-hole (-1)
- 22" (55.9 cm) x 18" (45.7 cm) x 34" (86.4 cm)


Codes/Standards Applicable

Specified model meets or exceeds the following:

- ADA
- ICC/ANSI A117.1
- CSA B651
- OBC
- ASME A112.19.2/CSA B45.1

WALL-MOUNT LAVATORY K-2035

ADA CSA B651 OBC



Colors/Finishes

- 0: White
- Other: Refer to Price Book for additional colors/finishes

Accessories

- CP: Polished Chrome
- Other: Refer to Price Book for additional colors/finishes

Specified Model

Model	Description	Colors/Fini	shes	
K-2035-8	Lavatory with 8" (20.3 cm) centers	0	☐ Other	
K-2035-4	Lavatory with 4" (10.2 cm) centers	0	☐ Other	
K-2035-1	Lavatory with single hole	0	□ Other	
Recommended Accessories				
K-7605-P	Lavatory supplies, 3/8" (pair)	□ CP	☐ Other	
	P-Trap	□ CP	□ Other	

Product Specification

The wall-mount lavatory shall be made of vitreous china. Lavatory shall be 22" (55.9 cm) in length, 18" (45.7 cm) in width, and 34" (86.4 cm) in height. Lavatory shall have 8" (20.3 cm) centers (-8), 4" (10.2 cm) centers (-4), or single hole (-1). Lavatory shall have overflow. Lavatory shall be Kohler Model K-2035-______.

PINOIR_®

Technical Information

Fixture*:				
Basin area	18" (45.7 cm) x 12" (30.5 cm)			
Water depth	4" (10.2 cm)			
Drain hole	1-3/4" (4.4 cm) D.			
* Approximate me	easurements for comparison only.			

Holes	K-2035-8	K-2035-4	K-2035-1
Spout	1-3/8" (3.5 cm) D.	1-1/4" (3.2 cm) D.	1-3/8" (3.5 cm) D.
Faucet	1-3/8" (3.5 cm) D.	1-1/4" (3.2 cm) D.	

Included components:	
Lavatory basin, 8" (20.3 cm) centers	K-2028-8
Lavatory basin, 4" (10.2 cm) centers	K-2028-4
Lavatory basin, single hole	K-2028-1
Shroud	K-2057
Rubber pads	63069
Hanger	64839
Shroud accessory pack	80265

Installation Notes

Install this product according to the installation guide.

Will comply with **ADA** when installed per section 606 Lavatories of the Act.

Will comply with **CSA B651** when installed per Clause 4.3.3 of the standard.

Will comply with **OBC** when installed per Clause 3.8.3.11.

