


Features

- Vitreous china
- Ledge-back
- With hanger
- With overflow
- Drilled for concealed arm carrier
- 8" (203 mm) centers (K-1724), 4" (102 mm) centers (K-1728) or single-hole (K-1722)
- 19-1/4" (489 mm) x 17-1/4" (438 mm)

Codes/Standards Applicable

Specified model meets or exceeds the following:

- ADA
- ASME A112.19.2/CSA B45.1
- ICC/ANSI A117.1



Colors/Finishes

- 0: White
- Other: Refer to Price Book for additional colors/finishes

Accessories:

CP: Polished Chrome

Model	Description	Colors/Finishes			
K-1724	8" (203 mm) centers bathroom sink	0 🗆 0	Other		
K-1728	4" (102 mm) centers bathroom sink	0	Other		
K-1722	Single-hole bathroom sink	0	□ Other		
Recommended Accessories					
K-8998	P-Trap	□ CP			

Specified Model

Product Specification

The wall-mount bathroom sink shall be made of vitreous china. Bathroom sink shall be ledge-back with hanger. Bathroom sink shall have overflow. Bathroom sink shall be drilled for concealed arm carrier. Bathroom sink shall have 8" (203 mm) centers (K-1724), 4" (102 mm) centers (K-1728), or single-hole (K-1722). Bathroom sink shall be 19-1/4" (489 mm) in length and 17-1/4" (430 mm) in width. Bathroom sink shall be Kohler Model K-______.

CHESAPEAKE_{TM}

WALL-MOUNT BATHROOM SINK K-1722 ALSO K-1724, K-1728

ADA

CHESAPEAKEтм

Technical Information

Fixture is ADA compliant.								
Fixture*:								
Basin area		14" (356 mm) x 11" (279 mm)						
Water depth		4-7/8" (124 mm)						
Drain hole		Ø 1-3/4" (44 mm)						
* Approximate measurements for comparison only.								
Holes	K-1724	Ļ	K-1728	K-1722				
Spout	Ø 1-3/8 (35 mn	-	Ø 1-1/4″ (32 mm)	Ø 1-3/8″ (35 mm)				
Faucet	Ø 1-3/8 (35 mn	-	Ø 1-1/4″ (32 mm)	NA				
Included component:								
Hanger	64839							

Installation Notes


Concealed Arm

Install this product according to the installation guide.

Concealed arm carrier NOT supplied by Kohler Co.

Supplied hanger not used with concealed arm carrier.

K-1724



K-1728 **Hole Locations** K-1722 4" (102 mm) 4" (102 mm) 2-1/2" (64 mm) 3-1/4" (83 mm) ±2-1/2" 2-1/2" (64 mm) (64 mm) 6-1/2" 8-1/2" (165 mm) (216 mm) 13-3/4" 17-1/4" ÌØ 1-1/4" (32 mm) (349 mm) (438 mm) Leveling € of Arm Carrier Screw Hole Ø 1-1/4" (32 mm) Ô 1-1/4" (32 mm) 15-3/8" 34" Leveling Screw 17-1/4" (438 mm) Locking Device (391 mm) (864 mm) Max Hole Hole 19-1/4" (489 mm) 1/4" (6 mm) 8-1/4" (210 mm) 10" (254 mm) 2" (51 mm) 13-3/4" 8-1/8" 32-1/8" 8" (206 mm) (349 mm) (816 mm) 3/8" Hot (203 mm) . Min 6" (152 mm) 30-1/4" 27" Max (768 mm) 3/8" Cold 31" (686 mm) . 4-1/2" (787 mm) Min 29-1/2" 9" (229 mm) 1-1/4" OD (114 mm) (749 mm) Min 4" (102 mm) **Recommended ADA Installation Standard Installation**

Product Diagram

