



Verdera®

20" x 34" arched framed medicine cabinet, left-hinged
K-36540

Features

- Front mirror, inside door mirror, and back panel mirror provide superior visibility to make grooming easier
- Two adjustable tempered-glass shelves offer additional bathroom storage
- Half-shelf adjustable accessory shelf for additional storage
- Finish-matched cabinet interior
- Hinges have 110° opening capability
- Box includes: Assembled mirrored cabinet, side panel kit, installation hardware



Material

- Anodized aluminum construction with a durable rustproof and chip-resistant finish
- KOHLER finishes resist corrosion and tarnishing

Installation

- Surface-mount or recessed
- Left-hand swing

Codes/Standards

None Applicable

KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color Code Description

	BGL	Moderne Brushed Gold
	BNL	Brushed Nickel
	CPL	Polished Chrome
	BLL	Matte Black

1-800-4KOHLER (1-800-456-4537)

Kohler Co. reserves the right to make revisions without notice to product specifications.


For the most current Specification Sheet, go to www.kohler.com USA or www.kohler.ca Canada

5-30-2025 01:30 - US/CA

THE BOLD LOOK
OF **KOHLER**®



Verdera®
20" x 34" arched framed medicine cabinet, left-hinged
K-36540



Technical Information

All product dimensions are nominal.

Lighting included: No

Notes

Install this product according to the installation guide.

Cutout for recess-mount installation: 17" (432 mm) width x 22-3/4" (578 mm) height.

IMPORTANT! For recess mounting, the wall cavity must be framed and cabinet secured to framing studs.

This cabinet is designed for left door swing. Check for obstructions.

CAUTION: Risk of property damage. For surface mounting, use anchors (not provided) rated for the loaded weight of this product.

Refer to the anchor manufacturer's instructions.

When determining the height of the medicine cabinet, ensure the mirrored door will clear all obstacles (such as a faucet). A minimum distance of 3" (76 mm) is required.