

Product Information

Applicable product:	
Comfort Height toilet - left-hand trip lever (shown)	K-3837
Comfort Height toilet - right-hand trip lever	K-3837-RA
Fixture:	
Configuration	two-piece, elongated
Water per flush	1.28 gpf (4.8 lpf)
Passageway	2-1/8" (54 mm)
Water area	11-1/2" (292 mm) x 8-3/4" (222 mm)
Water depth from rim	5-1/2" (140 mm)
Seat post hole centers	5-1/2" (140 mm)

Included components:	
Elongated bowl	K-4397
Tank	K-4438
Tank cover	1044820
Trip lever, left-hand OR	1126917
Trip lever, right-hand	1160317
Bolt cap accessory pack	1013092

Installation Notes

Install this product according to the installation guide.

For back-to-back toilet installations: Use only a 45° double wye fitting.

Will comply with the Americans with Disabilities Act (**ADA**) when installed per the requirements of the 2010 ADA Standards for Accessible Design, Section 604 Water Closets, of the Act. The Model Plumbing Codes require the installation of elongated open-front toilet seats in public bathrooms.

Will comply with **CSA B651** when installed per Clause 4.3.6 of the standard.

Will comply with **OBC** when installed per Clause 3.8.3.8 and 3.8.3.9.

Fixture conforms to ASME Standard A112.19.2/CSA B45.1. All dimensions are nominal.

