

Occasion™

Cross bathroom sink faucet handles K-27010-3

Features

- Two cross handles offer separate control of hot and cold water
- Part of the Occasion bathroom faucet and accessory collection
- UltraGlide® valves with dry-stem technology are designed to eliminate common leak paths and provide smooth, effortless control

Material

- Premium metal construction for durability and reliability
- KOHLER finishes resist corrosion and tarnishing

Installation

- For 8" 16" (203 406 mm) centers
- Deck-mount
- Handles are preassembled on valves to simplify installation

Required Products/Accessories

For above-counter installation

K-27008 Bathroom sink faucet spout with Cane design, 1.2 All ag gpm regul K-27008-K Bathroom sink faucet spout with Cane design, 1.0 ADA

gpm

K-27008-N Bathroom sink faucet spout with Cane design, 0.5 CSA B651 gpm OBC


K-27009 Bathroom sink faucet spout with Straight design, 1.2 gpm

K-27009-K Bathroom sink faucet spout with Straight design, 1.0 gpm

K-27009-N Bathroom sink faucet spout with Straight design, 0.5 gpm

Recommended Products/Accessories

K-23723 Faucet cleaner K-27060 18" towel bar K-27061 24" towel bar K-27062 24" double towel bar K-27063 Towel ring K-27064 Vertical toilet paper holder K-27065 Pivoting toilet paper holder K-27069 Robe hook K-27128 Toilet paper holder with tray





Codes/Standards

ASME A112.18.1/CSA B125.1 NSF/ANSI/CAN 61 NSF/ANSI/CAN 372 All applicable US Federal and State material regulations ADA ICC/ANSI A117.1 CSA B651 OBC

KOHLER[®] Faucet Lifetime Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.


Color	Code	Description
	CP	Polished Chrome
	SN	Vibrant® Polished Nickel
	BN	Vibrant® Brushed Nickel
	BL	Matte Black
	2MB	Vibrant® Brushed Moderne Brass
	BMB	Matte Black with Moderne Brass



KOHLER, Faucets

Occasion™

Cross bathroom sink faucet handles K-27010-3



Technical Information

All product dimensions are nominal.

Faucet:

Flow rate:1.2 gal/min (4.5 l/min)Pressure:60 psi (4.1 bar)Drain included:NoDrain with overflow:Yes

Notes

Install this product according to the installation instructions.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

