

#### Features

- 36" (914 mm) minimum base cabinet width.
- Single bowl.
- 5" (127 mm) depth provides easy accessibility.
- Rear offset drain increases workspace in the sink and storage space underneath.
- No faucet holes; requires wall- or deck-mount faucet.
- Matte finish offers rich, dimensional color.
- Includes K-6639 bottom sink rack.
- Sink drain and strainer sold separately.

#### Material

- KOHLER Neoroc composite material is thermal shock-resistant and heat-resistant to 750°F.
- Color-dense Neoroc material helps to minimize the appearance of scratches and stains.

#### Installation

- Undermount.

#### Recommended Products/Accessories

- K-8801 Sink drain and strainer with tailpiece
- K-8799 Sink drain and strainer basket
- K-23726 Drain treatment
- K-23730 Neoroc® cleaner

#### Optional Products/Accessories

- K-11352 Disposal Flange with Stopper
- K-9000 P-Trap

#### Included Components

- Additional Components:  
6639



ADA

#### Codes/Standards

CSA B45.5/IAPMO Z124  
ADA  
ICC/ANSI A117.1


#### KOHLER® Neoroc® Sinks Lifetime Limited Warranty

See website for detailed warranty information.

#### Available Colors/Finishes

*Color tiles intended for reference only.*

Color	Code	Description
	CM6	
	CM7	
	CM2	
	CM3	
	CM4	
	CM1	



#### Technical Information

All product dimensions are nominal.

Bowl configuration:	Single
Installation:	Undermount
Center(s):	4
Min. base cabinet width:	36" (914 mm)
Bowl area (Only):	Length: 30-1/2" (775 mm) Width: 15-5/16" (389 mm) Bowl depth: 5" (127 mm) Water depth: 5" (127 mm)
Number of deck holes:	1
Faucet hole spacing:	4" (102 mm)
Drain hole:	3-7/8" (98 mm)
Template:	Undermount, 1256394-7, required, included

#### Notes

Install this product according to the installation instructions.

**NOTICE:** Countertop manufacturer or cutter must use the cut-out template provided with the product, or a current one provided by Kohler Co. (call 1-800-4-KOHLER). Kohler Co. is not responsible for cutout errors when the incorrect cut-out template is used.

ADA compliant when installed to the specific requirements of these regulations.