

Provided in the control of the contr

Features

- Acts as an auxiliary interface for DTV Mode[™] or DTV Prompt[®] two-outlet digital interface.
- Provides simple on/off actuation of shower outlets.
- Sleek, minimalist design.

Installation

- Wall-mount.
- Intended for outside of showering space.

Required Products/Accessories

K-527 digital shower interface, portrait setting K-528-PM Two-port digital thermostatic valve

or

K-29200 wall-mount bath fill interface K-528-PM Two-port digital thermostatic valve

or

K-29201 wall-mount bath/shower interface K-528-PM Two-port digital thermostatic valve

or

K-29202 dual-outlet digital shower interface K-528-PM Two-port digital thermostatic valve

or

K-29204 Deck-mount bath fill interface K-528-PM Two-port digital thermostatic valve

or

K-29205 deck-mount bath/shower interface K-528-PM Two-port digital thermostatic valve

Recommended Products/Accessories

K-23723 Faucet cleaner

Included Components

Additional Components: Mounting hardware



Codes/Standards

UL 1951 CSA C22.2 No. 14 CSA C22.2 No. 68

KOHLER® Electronic Faucets, Valves, and Controls Five-Year Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes


Color tiles intended for reference only.


Color Code Description

CP Polished Chrome









Technical Information

All product dimensions are nominal.

Drain included: No

Max. Ambient temp: 104°F (40°C) Min. Operating temp: 86°F (30°C) Max. Operating temp: 120°F (48.9°C)

Max. Relative 100%

humidity condensing:

Notes

Install this product according to the installation instructions.

