

# Honesty™ Rite-Temp® Shower Valve Trim K-TS99764-4

### **Features**

- Includes face plate with handle, shower arm with flange and showerhead.
- Single handle controls both on/off activation and temperature setting.
- Supplied with ADA compliant metal lever handle.
- Includes single function 2.0 gpm (7.6 l/min) showerhead with Katalyst® Air Induction Technology.
- Showerhead features MasterClean<sup>™</sup> sprayface for easy cleaning.
- Complements the Honesty brand faucet collection.

### Material

- Premium material construction with metal handle ensures reliability and durability.
- KOHLER finishes resist corrosion and tarnishing, exceeding industry durability standards.

### Installation

Trim set requires valve to complete installation.

# **Required Accessories**

K-304/K-P304 Series Rite-Temp® Valves

or

K-8304/K-P8304 Series Rite-Temp® Valve & Cartridge Kits

or

K-8300/K-P8300 Series Rite-Temp® Valve Body Rough-ins K-8305/K-P8305 Series Rite-Temp® Cartridges

or

K-2971-KS 3/4" Pressure-balancing Valve

# **Optional Accessories**

K-10350 Deep Rough-In Kit For K-8305 Cartridges K-10351 Test Cap For K-8300 Series Valve Bodies







# Codes/Standards

ASME A112.18.1/CSA B125.1 DOE - Energy Policy Act 1992 EPA WaterSense® California Energy Commission (CEC)

# **KOHLER® Faucet Lifetime Limited Warranty**

See website for detailed warranty information.

# Available Color/Finishes

Color tiles intended for reference only.

Color Code Description




СР

Polished Chrome





# Honesty™ Rite-Temp® Shower Valve Trim K-TS99764-4



# **Technical Information**

All product dimensions are nominal.

# **Showerhead:**

Rated maximum flow: 2 gal/min (7.6 l/min) Pressure: 80 psi (5.5 bar)

### **Notes**

Install the product according to the installation guide.

NOTICE: Risk of product damage. Long screws for installing trim can damage the K-2971-KS valve. Consult the trim installation guide to verify if the thin wall installation kit (88526) is needed.

