

## Lighting Your Life Since 1970

Product Specifications - 1095BK			
Job Name:	Job Type:		
Quantity:	Comments		

and the same of th

1095BK 120" Pole

Finish	Glass/Shade	Product Category
Black		Outdoor Accessories

Lamping		Measurements		Shipping	
Number of Bulbs	N/A	Width	3.0"	Carton Weight	1.5 lbs
Light Type	N/A	Height	120.0"	Carton Width	4"
Bulb Type		Length	N/A	Carton Height	4"
Max Bulb Wattage	N/A	Extension	N/A	Carton Length	121"
Max Fixture Wattage		Back Plate Width	N/A	Carton Cubic Feet	0.88
Rated Life		Back Plate Height	N/A	Master Pack	1
Rated Lumens		НСО	N/A	Master Pack Weight	N/A
Color Temp		Min Overall Height	N/A	Master Pack Width	N/A
Bulb(s) Included	No	Max Overall Height	N/A	Master Pack Height	N/A
Light Up/Down	N/A	Hanging Weight	1.5 lbs	Master Pack Length	N/A
Beam Spread	N/A	Height Adjustable	N/A	Master Cubic Feet	N/A
CRI	N/A	Slope	N/A	UPS Shippable	
Photo Cell Included	N/A				
Ballast	N/A				

Certification		Other		Equivalents	
UL Standard	N/A	UPC Code	783209109513	Incandescent Watts	N/A
Energy Star	No	Shades Included	N/A	Fluorescent Watts	N/A
CA Title 24	No	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	No	Conversion Kit	N/A		
		Material	Aluminum		

Maxim Lighting International and all designs, logos and images © 2010 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Products are subject to revision in design and/or construction to conform to changes in UL and/or CSA and/or ETL standards, or that which may be required by law or availability of material.

Maxim Lighting International products are UL, ETL or CSA approved.

Dimmable

Color may vary from what is pictured above due to limitations inherent to photographic processes.

N/A

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.