

Lighting Your Life Since 1970

Glass/Shade

Product Specifications - 2001WT							
Job Name:	Job Type:						

Quantity:	Comments
-----------	----------

**Product Category** 

Outdoor Accessories



2001WT Cast Pier Mount

## *Finish* White

**Dark Sky** 

Lamping		Measurements		Shipping	
Number of Bulbs	N/A	Width	6.0"	Carton Weight	0.4 lbs
Light Type	N/A	Height	3.5"	Carton Width	6"
Bulb Type		Length	6.0"	Carton Height	4"
Max Bulb Wattage	N/A		N/A		6"
Max Fixture Wattage		Back Plate Width	N/A		0.07
Rated Life		Back Plate Height	N/A		8
Rated Lumens		НСО	N/A	Master Pack Weight	5.7 lbs
Color Temp		Min Overall Height	N/A	Master Pack Width	12.8"
Bulb(s) Included	No	Max Overall Height	N/A	Master Pack Height	7.5"
Light Up/Down	N/A	Hanging Weight	0.4 lbs	Master Pack Length	12.8"
Beam Spread	N/A	Height Adjustable	N/A		0.71
CRI	N/A	Slope	N/A	UPS Shippable	Yes
Photo Cell Included	N/A				
Ballast	N/A				
Dimmable	N/A				
Certification		Other		Equivalents	
UL Standard	N/A	UPC Code	783209200173	Incandescent Watts	N/A
Energy Star	No	Shades Included	N/A	Fluorescent Watts	N/A
CA Title 24	No	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	No	Conversion Kit	N/A		

Maxim Lighting International and all designs, logos and images © 2010 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Products are subject to revision in design and/or construction to changes in UL and/or CSA and/or ETL standards, or that which may be required by law or availability of material.

Aluminum

Maxim Lighting International products are UL, ETL or CSA approved.

Color may vary from what is pictured above due to limitations inherent to photographic processes.

N/A Material

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.