

Lighting Your Life Since 1970

Product Specifications - 51121FSBZ		
Job Name:	Job Type:	
Quantity:	Comments	



51121FSBZ **Knoxville LED 1-Light Outdoor** Pole/Post Lantern



Finish Bronze

Lamning

Lamping	
Number of Bulbs	1
Light Type	LED
Bulb Type	PCB Board
Max Bulb Wattage	15
Max Fixture Wattage	15
Rated Life	
Rated Lumens	±1,050
Color Temp	±3,000 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	N/A

Glass/Shade	
Frosted Seedy	y

Mea	sure	me	nts
mou	04.0		

Width	11.00"
Height	23.00"
Length	11.00"
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	0.00"
Max Overall Height	N/A
Hanging Weight	6.50 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Product Category

Outdoor Pole/Post Mount

Shinning

Jilippilig	
Carton Weight	7.10 lbs
Carton Width	14"
Carton Height	14"
Carton Length	20"
Carton Cubic Feet	2.30
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Cortification

Certification		Other	
Safety Rating	Wet	UPC Code	783209118928
Energy Star	No	Shades Included	N/A
CA Title 24	Yes	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	Yes	Material	N/A

Equivalents

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.