



Lighting Your Life Since 1970


## Product Specifications - 89984AL

Job Name:	Job Type:
Quantity:	Comments



### 89984AL

CounterMax MX-L-120-2K 18" 2700K or 3200K LED UC



#### Finish

Brushed Aluminum

#### Glass/Shade

#### Product Category

Under Cabinet

#### Lamping

Number of Bulbs	1
Light Type	LED
Bulb Type	PCB
Max Bulb Wattage	12
Max Fixture Wattage	12
Rated Life	
Rated Lumens	±840
Color Temp	2700/3200
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	90+
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	LED

#### Measurements

Width	3.25"
Height	1.25"
Length	18.00"
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	0.00"
Max Overall Height	N/A
Hanging Weight	1.33 lbs
Height Adjustable	No
Slope	N/A
Chain Length	N/A
Wire Length	6"
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

#### Shipping

Carton Weight	1.91 lbs
Carton Width	4"
Carton Height	2"
Carton Length	22"
Carton Cubic Feet	0.12
Master Pack	10
Master Pack Weight	19.10 lbs
Master Pack Width	12.50"
Master Pack Height	9.63"
Master Pack Length	22.50"
Master Cubic Feet	1.57
UPS Shippable	Yes

#### Certification

Safety Rating	Dry
Energy Star	No
CA Title 24	No
CA Title 20	No
ADA	No
Dark Sky	N/A

#### Other

UPC Code	783209127654
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	Metal+PC

#### Equivalents

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2016 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.