




Buy it for looks. Buy it for life.®

# Specifications



## 90 DEGREE™ Single-Handle Lavatory Faucet

**Models:** S6701  
S6701BN

**NOTE:** THIS FAUCET IS DESIGNED  
TO BE INSTALLED THROUGH 1  
HOLE, 1-1/8" MIN. DIA.



### DESCRIPTION

- Metal construction with various finishes identified by suffix
- Flexible supply lines with 3/8" compression fittings
- Includes metal pop-up waste assembly

### OPERATION

- Lever style handle
- Temperature controlled by 100° arc of handle travel

### FLOW

- Flow is limited to 1.0 gpm max (3.8L/min) at 60 psi

### CARTRIDGE

- 1255™ Duralast™ cartridge for Single-Handle Faucets

### STANDARDS

- Third party certified to WaterSense®, ASME A112.18.1/CSA B125.1, NSF 61/9 & 372 and all applicable requirements referenced therein
- Products marked with 1.0gpm are compliant with California water efficiency regulations
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- **ADA** ♿ for lever handle

### WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original homeowner
  - 10 year limited warranty when used in a multifamily installation
  - 5 year limited warranty when used in a commercial installation
- Visit [www.moen.com/support](http://www.moen.com/support) for complete details and limitations

