

AYLESBURY

Features

- Solid brass construction
- ADA compliant traditional cross handles
- 7-3/16" (18.3 cm) spout reach (wall-to-center)
- 1/2" NPT spout inlet fitting
- \bullet Intended for use with Newport Brass rough valve as specified (Required

Accessory)

- Rough valve incorporates a brass valve body assembly
- Rough valve incorporates quarter-turn washerless ceramic disc valve cartridges

Codes / Standards Compliance

Meets or exceeds the following at date of manufacture:

- ASME A112.18.1/CSA B125.1
- IAPMO/cUPC
- NSF 61
- IPC
- ADA
- ICC/ANSI A117.1
- Energy Policy Act of 1992
- All applicable US Federal and State material regulations
- EPA Watersense


Wall-Mounted Lavatory Faucet

3-2401









Colors / Finishes

15: Polished Nickel
15S: Satin Nickel
26: Polished Chrome
10B: Oil Rubbed Bronze

• Other: Refer to the Newport Brass catalog for additional color/finish options.

Specified Model

Model	Description	Colors / Finishes	
3-2401	Wall-Mounted Lavatory Faucet	□ 15 □ 15S □ 26 □ 10B	Other

Required Accessory: Faucet, above, and Rough Valve, below, must both be specified. Application Tub Only Valve* Wall Lavatory Valve Tub Only Valve* Wall Lavatory Valve 2-Cartridge Assembly with 16pt Spline Description 2-Cartridge Assembly with 20pt Spline Inlet/Outlet Size 1/2" 1/2" 1/2" 1/2" Part Number 1-500 1-560 1-532 1-564 Image

Product Specification:

Add "Color / Finish" suffix to model number, below.

The Wall-Mounted Lavatory Faucet shall be made of solid brass construction. Wall-Mounted Lavatory Faucet shall incorporate ADA compliant cross handles and a 7-3/16" (18.3 cm) spout (wall-to-center) that incorporates a 1/2" NPT inlet fitting. Rough valve shall incorporate a brass valve body assembly and quarter-turn washerless ceramic disc valve cartridges. Wall-Mounted Lavatory Faucet shall be Newport Brass Model 3-2401/_____ and Newport Brass rough valve shall be 1-532.

3-2401

Product Dimensions (units are in inches)

