

KIARA

Features

- · Solid brass construction
- ADA compliant traditional lever handles
- 7-1/4" (18.4 cm) spout length
- 3/4" NPT spout inlet fitting
- Intended for use with Newport Brass rough valve as specified (Required Accessory)
- Rough valve incorporates a brass valve body assembly
- Rough valve incorporates quarter-turn washerless ceramic disc valve cartridges

Codes / Standards Compliance

Meets or exceeds the following at date of manufacture:


- ASME A112.18.1/CSA B125.1
- IAPMO/cUPC
- IPC
- ADA
- ICC/ANSI A117.1
- All applicable US Federal and State material regulations

Wall-Mounted Tub Trim 3-2535









Colors / Finishes

15: Polished Nickel
15A: Antique Nickel
26: Polished Chrome
10B: Oil Rubbed Bronze

• Other: Refer to the Newport Brass catalog for additional color/finish options.

Specified Model					
Model	Description	Colors / Finishes			
3-2535	Wall-Mounted Tub Trim	☐ 15 ☐ 15A ☐ 26 ☐ 10B ☐ Other			

Required Ad	ccessory:	Both trim, above, and rough valve, below, must be specified.		
Application	Tub Only Valve*	Wall Lavatory Valve	Tub Only Valve*	Wall Lavatory Valve
Description	2-Cartridge Assembly with 16pt Spline		2-Cartridge Assembly with 20pt Spline	
Inlet/Outlet Size	1/2"	1/2"	1/2"	1/2"
Part Number	1-500	1-532	<u> </u>	1-560
Image			A CONTRACTOR OF THE PROPERTY O	

^{*} Plumbing code restrictions prohibit the use of the 1-564 for showers unless the 1-535 (Remote BP Valve) is installed upstream of the 1-564.

Product Specification:

The Wall-Mounted Tub Trim shall be made of solid brass construction. Wall-Mounted Tub Trim shall include ADA compliant lever handles and a 7-1/4" (18.4 cm) tub spout that incorporates a 3/4" NPT inlet fitting. Wall-Mounted Tub Trim shall be Newport Brass Model 3-2535/____ and Newport Brass rough valve shall be 1-564.

3-2535

Product Dimensions (units are in inches)

