

EAST LINEAR

1400-5412

Features

Bridge Style Kitchen Faucet with Sidespray

- Solid brass construction
- Bridge-style brass valve bodies
- Quarter-turn washerless ceramic disc valve cartridges
- ADA compliant contemporary cross handles
- Swivel spout assembly with integral diverter assembly
- Solid brass pull-out sidespray assembly
- 11-3/16" (21.2 cm) spout height at outlet
- 9" (22.8 cm) spout reach (c-c)
- For 8" (20.3 cm) centers
- 1.8 gallons (6.8 liters) per minute maximum flow rate

Codes / Standards Compliance

Meets or exceeds the following at date of manufacture:

- ASME A112.18.1/CSA B125.1
- IAPMO/cUPC
- IPC
- NSF 61
- NSF 372
- ADA (Handle Only)
- ICC/ANSI A117.1
- Energy Policy Act of 1992
- California Energy Commission (CEC)
- All applicable US Federal and State material regulations

Colors / Finishes

10B: Oil Rubbed Bronze
15: Polished Nickel
15S: Satin Nickel - PVD
26: Polished Chrome



Other: Refer to the Newport Brass catalog for additional color/finish options. Specified Model		
1400-5412	Bridge Style Kitchen Faucet with Sidespray	☐ 10B ☐ 15 ☐ 15S ☐ 26 ☐ Other

Product Specification Add "Color / Finish" suffix to Model number, below.

The Bridge Style Kitchen Faucet shall be made of solid brass construction. Faucet shall incorporate a swivel spout assembly with integral side-spray diverter assembly and feature bridge-style brass valve bodies with quarter-turn washerless ceramic disc valve cartridges. Faucet shall have a 1.8 gallons (6.8 liters) per minute maximum flow rate. Product shall be for 8" (20.3 cm) centers. Product shall incorporate a 11-3/16" (28.5 cm) spout height at outlet and a 9" (22.8 cm) spout reach (c-c). Faucet shall incorporate ADA compliant contemporary cross handles. Bridge-Style Kitchen Faucet with Sidespray shall be Newport Brass Model 1400-5412/____.

1400-5412

PRODUCT DIMENSIONS (Units are in inches)



