



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

65-626R1 - LED Canopy Fixture; 40 Watt; CCT Selectable; Bronze Finish

- CCT Selectable
- Has Driver



ELECTRICAL

Technology:	LED
Watts:	40W
Volts:	120V-277V
Lumens:	5785L/6215L/5909L
CRI:	80
CCT (Kelvins):	3000K/4000K/5000K
Temperature:	Warm to Cool White
Beam Spread :	150
Hours Rated:	50000
Dimmable:	Yes-Dimmable
DimmableText:	0-10V Dimming
Operating Temperature :	-40C (-40F) to +45C (+113F)
Number of LEDs :	75
Surge Protection :	Built-in surge protection - 4KV
THD:	?20%
Power Factor :	>0.9
Voltage Type:	Range Voltage
Warranty:	5 Year Limited - Fixtures

PACKAGING

Each UPC:	045923652288
Each Quantity:	1
Each Dimensions:	11.81 x 11.81 x 5.51
Case UPC:	10045923652285
Case Quantity:	2
Case Dimensions:	12.60 x 11.81 x 12.60

PHYSICAL

Finish:	Bronze
Lens Material:	Polycarbonate (PC)
Finish Family:	Bronze
Dimensions:	H:3.15" DIA:10.03"
Weight (Lbs.):	4.41
Material:	Die-cast Aluminum
Sensor:	Optional Add-On

COMPLIANCE

Safety Listing:	cULus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Outdoor
Energy Star Qualified:	No
DLC Approved:	Yes
DLC Classification:	Premium
DLC ID:	S-MUEZYA
DLC Primary Use:	Parking Garage Luminaires
CA Prop 65:	Lead
FCC Compliant:	Yes
IP Rating:	IP65
IK Rating:	IK10
RoHS Compliant:	Yes
SDS Class:	LED_Fixture
B.U.G Rating:	B2-U3-G2
Restrictions:	No Restrictions

INFO

Specification Note:	UV Stabilized Powder Coated Finish
---------------------	------------------------------------

ACCESSORIES

**65-638**Add on Emergency Backup Battery for LED Round Canopy Light Fixtures; 8 Watt; 90 min. Run Time; Black Finish

**86-217**Add-On PIR Sensor; 6 Meter

**86-218**Add-On Microwave Sensor; 12 Meter

**86-219**Programing Remote Control for use with 86-218, 86-217 & 86-220 Sensors

**86-220**Add-On PIR Sensor; 12 Meter

DIMMER COMPATIBILITY

LeGrand ADPD4FBL3P2W4

Eaton DF10P

Leviton DS710-10Z

Lutron DVSCSTV

Lutron DVSTV

Lutron MS-Z101

Lutron MS-Z101-V

Lutron NTSTV-DV

Eaton SF10P
