



Project/Job Name:

Location:

Fixture Type:

Notes:

**65-771R2** - Wattage 150W/175W/200W and CCT Selectable  
3K/4K/5K LED UFO High Bay; 100-277 Volt; Black Finish

• Wattage Selectable

• CCT Selectable



## ELECTRICAL

Technology:	LED
Watts:	150W/175W/200W
Volts:	120V-277V
Lumens:	22200L-28800L
Lamp Base :	Integrated
Lamp Shape :	Integrated LED
CRI:	80
CCT (Kelvins):	3000K/4000K/5000K
Temperature:	Warm White to Natural Light
Beam Spread :	90
Hours Rated:	50000
Dimmable:	Yes-Dimmable
DimmableText:	0-10V Dimming Only
Incandescent Equivalent :	1000W/1500W/2000W
HID Equivalent :	400W-450W
Operating Temperature :	-40C (-40F) to +50C (+122F)
Lamp Included :	Integrated
Replaceable Light Source :	No
Number of LEDs :	640
Surge Protection :	Built-in surge protection - 6KV
THD:	15%
Power Factor :	0.9
Voltage Type:	Range Voltage
Warranty:	5 Year Limited - Fixtures

## PACKAGING

Each UPC:	045923648304
Each Quantity:	1
Each Dimensions:	14.17 x 14.17 x 4.92
Case UPC:	10045923648301
Case Quantity:	1
Case Dimensions:	14.17 x 14.17 x 7.99

## PHYSICAL

Finish:	Black
Lens Finish:	Clear
Lens Material:	Polycarbonate (PC)
Finish Family:	Black
Dimensions:	H:7.30" DIA:13.40"
Weight (Lbs.):	6.42
Material:	Die-cast Aluminum
Sensor:	Optional Add-On

## INSTALLATION

Wire Length:	72 in.
--------------	--------

## COMPLIANCE

Safety Listing:	cULus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor
Energy Star Qualified:	No
DLC Approved:	Yes
DLC Classification:	Premium
DLC ID:	S-KCEODI
DLC Primary Use:	High-Bay Luminaires for Commercial and Industrial Buildings
UL/ETL Standard:	UL 1598; CSA-C22.2 No. 250.0
CA Prop 65:	Lead
FCC Compliant:	Yes
IP Rating:	IP65
IK Rating:	IK08
NSF Approved:	Yes
RoHS Compliant:	Yes
SDS Class:	LED_Fixture
Restrictions:	No Restrictions

## INFO

Specification Note:

Installation Note:

Input Current at 120V: 1.69A

Mounting Height: Up to 30 feet

SATCO.COM | 800-437-2826

© Satco Products, Inc.  
All rights reserved 2023

Includes:	Locking Hanging Hook; 6 Foot Whip
-----------	-----------------------------------

## ACCESSORIES

	<b>65-169</b>	Whip Connector; 5.5 Foot; IP68 Rated; Black; 0-10V Dimming
	<b>65-199</b>	Whip Connector; 5.5 ft.; IP68 Rated; Black
	<b>65-766</b>	Yoke Mount Bracket; Black Finish; For Use With Gen 2 200W/240W & CCT & Wattage Selectable UFO High Bay Fixtures
	<b>65-769</b>	3/8" to 3/4" Pendant Adapter; Black Finish; For use with Gen 2 and CCT & Wattage Selectable UFO LED High Bay Fixtures
	<b>65-779</b>	Add-On Aluminum Reflector; Use with 200W & 240W Gen 2 UFO LED High Bay Fixtures
	<b>65-799</b>	Add-On PC Shade; Use with 200W & 240W Gen 2 UFO LED High Bay Fixtures
	<b>65-800</b>	Add-On Bottom Diffuser for 200W & 240W Gen 2 UFO LED High Bay Fixtures. Note, must be used in conjunction with 65-799 (PC Shade)
	<b>65-810</b>	Protective Wire Guard for 200W & 240W Gen 2 UFO LED High Bay Fixtures
	<b>65-815</b>	40W Add-On EM Battery Backup; For use with Gen 2 200W/240W and 65/771R1 CCT & Wattage Selectable UFO LED High Bay Fixtures; 40 Watt /90 Min Run Time
	<b>86-217</b>	Add-On PIR Sensor; 6 Meter
	<b>86-218</b>	Add-On Microwave Sensor; 12 Meter
	<b>86-219</b>	Programing Remote Control for use with 86-218, 86-217 & 86-220 Sensors
	<b>86-220</b>	Add-On PIR Sensor; 12 Meter



**65-771R2** - Wattage 150W/175W/200W and CCT Selectable  
3K/4K/5K LED UFO High Bay; 100-277 Volt; Black Finish

#### DIMMER COMPATIBILITY

LeGrand	ADPD4FBL3P2W4
---------	---------------

Eaton	DF10P
-------	-------

Leviton	DS710-10Z
---------	-----------

Lutron	DVSCSTV
--------	---------

Lutron	DVSTV
--------	-------

Lutron	DVTV PP347H 347V Only
--------	-----------------------

Leviton	IP710-LFZ
---------	-----------

Lutron	MS-Z101
--------	---------

Lutron	MS-Z101-V
--------	-----------

Lutron	NTSTV-DV
--------	----------

Lutron	RMJS-8T-DV-B PJ2-3BRL-GWH-L01
--------	-------------------------------

Eaton	SF10P
-------	-------