



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

65-784R2 - 150 Watt UFO LED High Bay; 5000K; 21600 Lumens;
120-277 Volt; Black Finish



ELECTRICAL

| | |
|----------------------------|---------------------------------|
| Technology: | LED |
| Watts: | 150W |
| Volts: | 120V-277V |
| Lumens: | 21600L |
| Lamp Base : | Integrated |
| Lamp Shape : | Integrated LED |
| CRI: | 80 |
| CCT (Kelvins): | 5000K |
| Temperature: | Natural Light |
| Beam Spread : | 90 |
| Hours Rated: | 50000 |
| Dimmable: | Yes-Dimmable |
| DimmableText: | 0-10V Dimming Only |
| Incandescent Equivalent : | 1000W |
| HID Equivalent : | 400W |
| Operating Temperature : | -40C (-40F) to +50C (+122F) |
| Lamp Included : | Integrated |
| Replaceable Light Source : | No |
| Number of LEDs : | 425 |
| Surge Protection : | Built-in surge protection - 6KV |
| THD: | 15% |
| Power Factor : | 0.9 |
| Voltage Type: | Range Voltage |
| Warranty: | 5 Year Limited - Fixtures |

PACKAGING

| | |
|------------------|----------------------|
| Each UPC: | 045923648083 |
| Each Quantity: | 1 |
| Each Dimensions: | 11.81 x 11.81 x 4.92 |
| Case UPC: | 10045923648080 |
| Case Quantity: | 1 |
| Case Dimensions: | 11.81 x 11.81 x 5.72 |

PHYSICAL

| | |
|----------------|--------------------|
| Finish: | Black |
| Lens Material: | Polycarbonate (PC) |
| Finish Family: | Black |
| Dimensions: | H:8.11" DIA:11.02" |
| Weight (Lbs.): | 4.53 |
| Material: | Die-cast Aluminum |
| Sensor: | Optional Add-On |

INSTALLATION

| | |
|--------------|--------|
| Wire Length: | 72 in. |
|--------------|--------|















COMPLIANCE

| | |
|------------------------|---|
| Safety Listing: | cULus - Listed |
| Location Rating: | Wet |
| Indoor/Outdoor: | Indoor |
| Energy Star Qualified: | No |
| DLC Approved: | Yes |
| DLC Classification: | Premium |
| DLC ID: | S-KPFT1H |
| DLC Primary Use: | High-Bay Luminaires for Commercial and Industrial Buildings |
| UL/ETL Standard: | UL 1598; CSA-C22.2 No. 250.0 |
| CA Prop 65: | Lead |
| FCC Compliant: | Yes |
| IP Rating: | IP65 |
| IK Rating: | IK08 |
| NSF Approved: | Yes |
| RoHS Compliant: | Yes |
| SDS Class: | LED_Fixture |
| Restrictions: | No Restrictions |

INFO

| | |
|--------------------|-----------------------------------|
| Installation Note: | Mounting Height: Up to 25 feet |
| Includes: | Locking Hanging Hook; 6 Foot Whip |

ACCESSORIES

| | | |
|--|---------------|--|
|  | 65-169 | Whip Connector; 5.5 Foot; IP68 Rated; Black; 0-10V Dimming |
|  | 65-199 | Whip Connector; 5.5 ft.; IP68 Rated; Black |
|  | 65-765 | Yoke Mount Bracket; Black Finish; For Use With Gen 2 100W/150W & CCT & Wattage Selectable UFO High Bay Fixtures |
|  | 65-769 | 3/8" to 3/4" Pendant Adapter; Black Finish; For use with Gen 2 and CCT & Wattage Selectable UFO LED High Bay Fixtures |
|  | 65-778 | Add-On Aluminum Reflector; Use with 100W & 150W Gen 2 UFO LED High Bay Fixtures |
|  | 65-780 | Add-On EM Battery Backup; For use with Gen 2 100W/150W and 65/770R1 CCT & Wattage Selectable UFO LED High Bay Fixtures; 30 Watt /90 Min Run Time |
|  | 65-789 | Add-On PC Shade; Use with 100W & 150W Gen 2 UFO LED High Bay Fixtures |
|  | 65-790 | Add-On Bottom Diffuser for 100W & 150W Gen 2 UFO LED High Bay Fixtures. Note, must be used in conjunction with 65-789 (PC Shade) |
|  | 65-809 | Protective Wire Guard for 100W & 150W Gen 2 UFO LED High Bay Fixtures |
|  | 65-811 | Add-On PC Shade; Use with 100W & 150W UFO LED High Bay Fixtures |
|  | 86-217 | Add-On PIR Sensor; 6 Meter |
|  | 86-218 | Add-On Microwave Sensor; 12 Meter |
|  | 86-219 | Programing Remote Control for use with 86-218, 86-217 & 86-220 Sensors |
|  | 86-220 | Add-On PIR Sensor; 12 Meter |



65-784R2 - 150 Watt UFO LED High Bay; 5000K; 21600 Lumens;
120-277 Volt; Black Finish

DIMMER COMPATIBILITY

| | |
|---------|---------------|
| LeGrand | ADPD4FBL3P2W4 |
|---------|---------------|

| | |
|-------|-------|
| Eaton | DF10P |
|-------|-------|

| | |
|---------|-----------|
| Leviton | DS710-10Z |
|---------|-----------|

| | |
|--------|---------|
| Lutron | DVSCSTV |
|--------|---------|

| | |
|--------|-------|
| Lutron | DVSTV |
|--------|-------|

| | |
|--------|-----------------------|
| Lutron | DVTV PP347H 347V Only |
|--------|-----------------------|

| | |
|---------|-----------|
| Leviton | IP710-LFZ |
|---------|-----------|

| | |
|--------|---------|
| Lutron | MS-Z101 |
|--------|---------|

| | |
|--------|-----------|
| Lutron | MS-Z101-V |
|--------|-----------|

| | |
|--------|----------|
| Lutron | NTSTV-DV |
|--------|----------|

| | |
|--------|-------------------------------|
| Lutron | RMJS-8T-DV-B PJ2-3BRL-GWH-L01 |
|--------|-------------------------------|

| | |
|-------|-------|
| Eaton | SF10P |
|-------|-------|