



Project/Job Name:

Location:

Fixture Type:

Notes:

65-795R2 - 200 Watt UFO LED High Bay; 4000K; 28000 Lumens; 120-277 Volt; White Finish



ELECTRICAL

Technology:	LED
Watts:	200W
Volts:	120V-277V
Lumens:	28000L
Lamp Base :	Integrated
Lamp Shape :	Integrated LED
CRI:	80
CCT (Kelvins):	4000K
Temperature:	Cool White
Beam Spread :	90
Hours Rated:	50000
Dimmable:	Yes-Dimmable
DimmableText:	0-10V Dimming Only
Incandescent Equivalent :	1500W
HID Equivalent :	600W
Operating Temperature :	-40C (-40F) to +50C (+122F)
Lamp Included :	Integrated
Replaceable Light Source :	No
Number of LEDs :	595
Surge Protection :	Built-in surge protection - 6KV
THD:	15%
Power Factor :	0.9
Voltage Type:	Range Voltage
Warranty:	5 Year Limited - Fixtures

PACKAGING

Each UPC:	045923648250
Each Quantity:	1
Each Dimensions:	14.17 x 14.17 x 4.92
Case UPC:	10045923648257
Case Quantity:	1
Case Dimensions:	14.17 x 14.17 x 7.99

PHYSICAL

Finish:	White
Lens Material:	Polycarbonate (PC)
Finish Family:	White
Dimensions:	H:8.11" DIA:13.39"
Weight (Lbs.):	6.42
Material:	Die-cast Aluminum
Sensor:	Optional Add-On

INSTALLATION

Wire Length:	72 in.
--------------	--------













COMPLIANCE

Safety Listing:	cULus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor
Energy Star Qualified:	No
DLC Approved:	Yes
DLC Classification:	Premium
DLC ID:	S-UTS1HQ
DLC Primary Use:	High-Bay Luminaires for Commercial and Industrial Buildings
UL/ETL Standard:	UL 1598; CSA-C22.2 No. 250.0
CA Prop 65:	Lead
FCC Compliant:	Yes
IP Rating:	IP65
IK Rating:	IK08
NSF Approved:	Yes
RoHS Compliant:	Yes
SDS Class:	LED_Fixture
Restrictions:	No Restrictions

INFO

Installation Note:	Mounting Height: Up to 30 feet
Includes:	Locking Hanging Hook; 6 Foot Whip

ACCESSORIES

	65-170	Whip Connector; 5.5 Foot; IP68 Rated; White; 0-10V Dimming
	65-200	Whip Connector; 5.5 ft.; IP68 Rated; White
	65-759	3/8" to 3/4" Pendant Adapter; White Finish; For use with Gen 2 and CCT & Wattage Selectable UFO LED High Bay Fixtures
	65-764	Yoke Mount Bracket; White Finish; For Use With Gen 2 200W/240W and CCT & Wattage Selectable UFO High Bay Fixtures
	65-779	Add-On Aluminum Reflector; Use with 200W & 240W Gen 2 UFO LED High Bay Fixtures
	65-799	Add-On PC Shade; Use with 200W & 240W Gen 2 UFO LED High Bay Fixtures
	65-800	Add-On Bottom Diffuser for 200W & 240W Gen 2 UFO LED High Bay Fixtures. Note, must be used in conjunction with 65-799 (PC Shade)
	65-810	Protective Wire Guard for 200W & 240W Gen 2 UFO LED High Bay Fixtures
	65-815	40W Add-On EM Battery Backup; For use with Gen 2 200W/240W and 65/771R1 CCT & Wattage Selectable UFO LED High Bay Fixtures; 40 Watt /90 Min Run Time
	86-217	Add-On PIR Sensor; 6 Meter
	86-218	Add-On Microwave Sensor; 12 Meter
	86-219	Programing Remote Control for use with 86-218, 86-217 & 86-220 Sensors
	86-220	Add-On PIR Sensor; 12 Meter



65-795R2 - 200 Watt UFO LED High Bay; 4000K; 28000 Lumens; 120-277 Volt; White Finish

DIMMER COMPATIBILITY

LeGrand	ADPD4FBL3P2W4
Eaton	DF10P
Leviton	DS710-10Z
Lutron	DVSCSTV
Lutron	DVSTV
Lutron	DVTV PP347H 347V Only
Leviton	IP710-LFZ
Lutron	MS-Z101
Lutron	MS-Z101-V
Lutron	NTSTV-DV
Lutron	RMJS-8T-DV-B PJ2-3BRL-GWH-L01
Eaton	SF10P