



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**65-805R2** - 200 Watt UFO LED High Bay; 4000K; 28200 Lumens;  
277-480 Volt; Black Finish



### ELECTRICAL

Technology:	LED
Watts:	200W
Volts:	277V-480V
Lumens:	28200L
Lamp Base :	Integrated
Lamp Shape :	Integrated LED
CRI:	80
CCT (Kelvins):	4000K
Temperature:	Cool White
Beam Spread :	90
Hours Rated:	50000
Dimmable:	Yes-Dimmable
DimmableText:	0-10V Dimming Only
Incandescent Equivalent :	1500W
HID Equivalent :	600W
Operating Temperature :	-40C (-40F) to +45C (+113F)
Lamp Included :	Integrated
Replaceable Light Source :	No
Number of LEDs :	595
Surge Protection :	Built-in surge protection - 6KV
THD:	15%
Power Factor :	0.9
Voltage Type:	Range Voltage
Warranty:	5 Year Limited - Fixtures

### PACKAGING

Each UPC:	045923648175
Each Quantity:	1
Each Dimensions:	14.17 x 14.17 x 4.92
Case UPC:	10045923648172
Case Quantity:	1
Case Dimensions:	14.17 x 14.17 x 4.92

### PHYSICAL

Finish:	Black
Lens Material:	Polycarbonate (PC)
Finish Family:	Black
Dimensions:	H:8.11" DIA:13.39"
Weight (Lbs.):	10.11
Material:	Die-cast Aluminum
Sensor:	Optional Add-On

### INSTALLATION

Wire Length:	72 in.
--------------	--------












### COMPLIANCE

Safety Listing:	cULus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor
Energy Star Qualified:	No
DLC Approved:	Yes
DLC Classification:	Premium
DLC ID:	S-XVEN4G
DLC Primary Use:	High-Bay Luminaires for Commercial and Industrial Buildings
CA Prop 65:	Lead
FCC Compliant:	Yes
IP Rating:	IP65
IK Rating:	IK08
NSF Approved:	Yes
RoHS Compliant:	Yes
SDS Class:	LED_Fixture
Restrictions:	No Restrictions

### INFO

Installation Note:	Mounting Height: Up to 30 feet
Includes:	Locking Hanging Hook; 6 Foot Whip

## ACCESSORIES

	<b>65-169</b>	Whip Connector; 5.5 Foot; IP68 Rated; Black; 0-10V Dimming
	<b>65-199</b>	Whip Connector; 5.5 ft.; IP68 Rated; Black
	<b>65-766</b>	Yoke Mount Bracket; Black Finish; For Use With Gen 2 200W/240W & CCT & Wattage Selectable UFO High Bay Fixtures
	<b>65-769</b>	3/8" to 3/4" Pendant Adapter; Black Finish; For use with Gen 2 and CCT & Wattage Selectable UFO LED High Bay Fixtures
	<b>65-779</b>	Add-On Aluminum Reflector; Use with 200W & 240W Gen 2 UFO LED High Bay Fixtures
	<b>65-799</b>	Add-On PC Shade; Use with 200W & 240W Gen 2 UFO LED High Bay Fixtures
	<b>65-800</b>	Add-On Bottom Diffuser for 200W & 240W Gen 2 UFO LED High Bay Fixtures. Note, must be used in conjunction with 65-799 (PC Shade)
	<b>65-810</b>	Protective Wire Guard for 200W & 240W Gen 2 UFO LED High Bay Fixtures
	<b>65-815</b>	40W Add-On EM Battery Backup; For use with Gen 2 200W/240W and 65/771R1 CCT & Wattage Selectable UFO LED High Bay Fixtures; 40 Watt /90 Min Run Time
	<b>86-218</b>	Add-On Microwave Sensor; 12 Meter
	<b>86-219</b>	Programing Remote Control for use with 86-218, 86-217 & 86-220 Sensors