

## Pivot LED

Wall or Ceiling Mounted • Damp Location Listed **PROGRESS LED**

### Description:

Pivot LED Four-Light Burnished Nickel Modern Semi-Flush or Wall Mount Fixture

### Specifications:

- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 5.125 in W., 1.25 in ht., 5.125 in depth
- Mounting backplate for outlet box included
- 6 in of wire supplied

### Performance:

Number of Modules	4
Input Power	17.5 W
Input Voltage	120 VAC
Input Frequency	60 Hz
Lumens/LPW (Delivered)	930/53 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	50000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Warranty	5-year Limited Warranty
Labels	cETLus Damp Location Listed Meets California Title 24 JA8-2016

# P350230-186-30



### Dimensions:

Diameter: 25 in  
Height: 4-3/8 in

# P350230-186-30

**Photometrics:**

---

<b>ELECTRICAL DATA</b>	<b>P350230-186-30</b>
Input Voltage	120 VAC
Input Frequency	60 Hz
THD	<20%
EMI/RFI	FCC Title 47, Part 15, Class B
Operating Temperature	-30 °C to 30 °C
Dimming	Yes*
Over-voltage, over-current, short-circuit protected	
*See Dimming Notes for more information	

# P350230-186-30

**Dimming Notes:**

---

P350230-186-30 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

**Dimming Controls:**

---

Lutron NTEVL-300

Lutron DVELV-300P

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.