

LED DOME

Ceiling mounted • Damp location listed



Description:

A domed, linen finish glass diffuser is discreetly supported from metal fittings and encloses an energy-efficient light source.

Specifications:

- Brushed Nickel (-009) (plated)
- Steel construction
- Etched White Linen glass diffuserDesign features a domed, linen finish glass diffuser.
- Diffuser is discreetly supported from metal fittings encloses an energy-efficient light source
- Brushed Nickel finish.
- 1600 lumens 83 lumens/watt
- 3000K color temperature, 90+ CRI
- Dimmable to 10% brightness (See Dimming Notes)
- covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- ENERGY STAR® qualified

Performance:

Number of Modules	1
Input Power	20w
Input Voltage	120 V
Input Frequency	
Lumens/LPW	1000/83 (LM-79)
CCT	3000 K
CRI	
Life (hours)	(L70/TM-21)
EMI/RFI	
Min. Start Temp	
Max. Operating Temp	
Warranty	
Labels	cETLus Damp location listed ENERGY STAR® qualified

P350055-009-30

Images:



Dimensions:

Diameter: 12"
Height: 4-1/4"

Glass
Width: 11-3/4"
Height: 3"