

Project:	
Fixture Type:	
Location:	
Contact:	

MINGLE LED

Ceiling mount · Damp location listed

PROGRESS	LE	D)
	<u></u> _	\mathcal{I}



Specifications:

Description:

One-light LED semi- flush mount features a modern circular/square pattern in an Antique Bronze metal shade that surrounds a summer linen fabric shade with a glass diffuser. 3000K, 90+ CRI 1,211 Lumens 71.2 lumen/watt

Construction:

Antique Bronze (-20) (painted)

Steel construction

Fabric Shade glass shade

LED Module is replaceable (part # 93053641)

Flicker-free dimming to 10% brightness with most ELV type dimmers

(See Dimming Notes)

Title 24 compliant

Canopy covers a standard 4" hexagonal recessed outlet box

Mounting strap for outlet box included

Six inches of wire supplied

Performance:

Number of Modules	1
Input Power	17W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	1211/71.2 (LM-79) per module
CCT	3000K
CRI	90+
Life	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	cCSAus Damp location listed
	ENERGY STAR® qualified

P2329-2030K9

Images:



Dimensions:

Diameter: 14" Height: 10-1/2"

Catalog number:

Base		Finish	Color Temp	CRI
P2329	-	20 - Antique Bronze	30K - 3000K	9 - 90 CRI