

MINGLE LED

Ceiling mount • Damp location listed

Specifications:

Description:

One-light LED flush mount features a modern square pattern in a Brushed Nickel metal shade that surrounds a summer linen fabric shade with a glass diffuser. 3000K, 90+ CRI 1,211 Lumens 71.2 lumen/watt

Construction:

Brushed Nickel (-09) (plated)
 Steel construction
 Fabric Shade glass shade
 LED Module is replaceable (part # 93053641)
 Flicker-free dimming to 10% brightness with most ELV type dimmers
 (See Dimming Notes)
 Title 24 compliant
 Canopy covers a standard 4" hexagonal recessed outlet box
 Mounting strap for outlet box included
 Six inches of wire supplied

Performance:

Number of Modules	1
Input Power	17W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	1211/71.2 (LM-79) per module
CCT	3000K
CRI	90+
Life	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	cCSAus Damp location listed ENERGY STAR® qualified

P2330-0930K9

Images:



Dimensions:

Diameter: 11"
 Height: 5-7/8"

Catalog number:

Base	Finish	Color Temp	CRI
P2330	09 - Brushed Nickel	30K - 3000K	9 - 90 CRI